

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.024.030.0325	2.4	0.30	3.25	90	5.31	0.0590	9.6	1.28	1.40	4E
D.026.030.0975	2.6	0.30	9.75	270	5.31	0.0197	10.4	3.23	1.60	4E
D.028.020.0350	2.8	0.20	3.50	180	1.17	0.0073	11.2	0.90	1.80	4E
D.028.020.0525	2.8	0.20	5.25	90	1.11	0.0051	11.2	1.25	1.80	4E
D.028.020.0775	2.8	0.20	7.75	270	1.11	0.0035	11.2	1.75	1.80	4E
D.028.020.1200	2.8	0.20	12.00	0	1.11	0.0023	11.2	2.60	1.80	4E
D.028.030.0600	2.8	0.30	6.00	0	5.31	0.0295	11.2	2.10	1.70	4E
D.028.032.0350	2.8	0.32	3.50	180	4.15	0.0495	11.2	1.44	1.50	4E
D.028.032.0525	2.8	0.32	5.25	90	4.15	0.0346	11.2	2.00	1.50	4E
D.028.032.0775	2.8	0.32	7.75	270	4.15	0.0243	11.2	2.80	1.50	4E
D.028.032.1200	2.8	0.32	12.00	0	4.15	0.0161	11.2	4.16	1.50	4E
D.028.040.0425	2.8	0.40	4.25	90	10.51	0.1168	11.2	2.10	1.60	4E
D.032.022.0350	3.2	0.22	3.50	180	1.49	0.0093	12.8	0.99	2.10	4E
D.032.022.0525	3.2	0.22	5.25	90	1.49	0.0065	12.8	1.38	2.10	4E
D.032.022.0575	3.2	0.22	5.75	270	1.49	0.0045	12.8	1.49	2.10	4E
D.032.022.0775	3.2	0.22	7.75	270	1.49	0.0045	12.8	1.93	2.29	4E
D.032.022.1200	3.2	0.22	12.00	0	1.49	0.0030	12.8	2.86	2.10	4E
D.032.035.0350	3.2	0.35	3.50	180	5.46	0.0617	12.8	1.58	1.80	4E
D.032.035.0525	3.2	0.35	5.25	90	5.46	0.0432	12.8	2.19	1.80	4E
D.032.035.0775	3.2	0.35	7.75	270	5.46	0.0302	12.8	3.06	1.80	4E
D.032.035.1200	3.2	0.35	12.00	0	5.46	0.0200	12.8	4.55	1.80	4E
D.032.036.0325	3.2	0.36	3.25	90	7.91	0.0879	12.8	1.53	1.60	4E
D.032.036.1075	3.2	0.36	10.75	270	7.91	0.0293	12.8	4.23	1.60	4E
D.032.040.0975	3.2	0.40	9.75	270	10.51	0.0389	12.8	4.30	2.00	4E
D.033.040.0600	3.3	0.40	6.00	0	10.51	0.0584	13.2	2.80	2.00	4E
D.034.036.0700	3.4	0.36	7.00	0	7.91	0.0439	13.6	2.88	2.00	4E
D.035.050.0200	3.5	0.50	2.00	0	17.18	0.5254	14.0	1.50	2.25	4E
D.035.050.0325	3.5	0.50	3.25	90	17.18	0.3229	14.0	2.13	2.25	4E
D.035.050.0450	3.5	0.50	4.50	180	17.18	0.2331	14.0	2.75	2.25	4E
D.035.050.0575	3.5	0.50	5.75	270	17.18	0.1826	14.0	3.38	2.25	4E
D.035.050.0700	3.5	0.50	7.00	0	17.18	0.1499	14.0	4.00	2.25	4E
D.035.050.0825	3.5	0.50	8.25	90	17.18	0.1273	14.0	4.63	2.25	4E
D.035.050.0950	3.5	0.50	9.50	180	17.18	0.1105	14.0	5.25	2.25	4E
D.035.050.1075	3.5	0.50	10.75	270	17.18	0.0976	14.0	5.88	2.25	4E
D.036.025.0350	3.6	0.25	3.50	180	2.08	0.0137	14.4	1.13	2.30	4E
D.036.025.0525	3.6	0.25	5.25	90	2.08	0.0096	14.4	1.56	2.30	4E
D.036.025.0775	3.6	0.25	7.75	270	2.08	0.0067	14.4	2.19	2.30	4E
D.036.025.1200	3.6	0.25	12.00	0	2.08	0.0044	14.4	3.25	2.30	4E
D.036.040.0350	3.6	0.40	3.50	180	8.14	0.0937	14.4	1.80	2.00	4E
D.036.040.0525	3.6	0.40	5.25	90	8.14	0.0656	14.4	2.50	2.00	4E
D.036.040.0775	3.6	0.40	7.75	270	8.14	0.0459	14.4	3.50	2.00	4E
D.036.040.1200	3.6	0.40	12.00	0	8.14	0.0304	14.4	5.20	2.00	4E
D.040.028.0350	4.0	0.28	3.50	180	2.92	0.0195	16.0	1.26	2.60	4E
D.040.028.0525	4.0	0.28	5.25	90	2.92	0.0136	16.0	1.75	2.60	4E
D.040.028.0775	4.0	0.28	7.75	270	2.92	0.0095	16.0	2.45	2.60	4E
D.040.028.1200	4.0	0.28	12.00	0	2.92	0.0063	16.0	3.64	2.60	4E
D.040.045.0350	4.0	0.45	3.50	180	11.01	0.1352	16.0	2.03	2.30	4E
D.040.045.0525	4.0	0.45	5.25	90	11.01	0.0947	16.0	2.81	2.30	4E
D.040.045.0775	4.0	0.45	7.75	270	11.01	0.0663	16.0	3.94	2.30	4E
D.040.045.1200	4.0	0.45	12.00	0	11.01	0.0439	16.0	5.85	2.30	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.041.045.0325	4.1	0.45	3.25	90	13.22	0.1469	16.4	1.91	2.40	4E
D.041.045.0975	4.1	0.45	9.75	270	13.22	0.0490	16.4	4.84	2.40	4E
D.041.045.1075	4.1	0.45	10.75	270	15.82	0.0586	16.4	5.29	2.80	4E
D.042.030.0400	4.2	0.30	4.00	0	5.31	0.0295	16.8	1.50	2.80	4E
D.042.045.0700	4.2	0.45	7.00	0	15.82	0.0879	16.8	3.60	2.80	4E
D.043.030.0475	4.3	0.30	4.75	270	5.31	0.0197	17.2	1.73	2.80	4E
D.044.030.0650	4.4	0.30	6.50	180	5.31	0.0148	17.6	2.25	2.80	4E
D.044.045.0600	4.4	0.45	6.00	0	13.22	0.0734	17.6	3.15	2.40	4E
D.044.050.1175	4.4	0.50	11.75	270	21.10	0.0781	17.6	6.38	2.40	4E
D.045.032.0350	4.5	0.32	3.50	180	4.35	0.0296	18.0	1.44	2.90	4E
D.045.032.0525	4.5	0.32	5.25	90	4.35	0.0207	18.0	2.00	2.90	4E
D.045.032.0775	4.5	0.32	7.75	270	4.35	0.0144	18.0	2.80	2.90	4E
D.045.032.1200	4.5	0.32	12.00	0	4.35	0.0096	18.0	4.16	2.90	4E
D.045.045.0325	4.5	0.45	3.25	90	15.82	0.1758	18.0	1.91	2.80	4E
D.045.050.0200	4.5	0.50	2.00	0	17.18	0.3940	18.0	1.50	3.15	4E
D.045.050.0325	4.5	0.50	3.25	90	17.18	0.2423	18.0	2.13	3.15	4E
D.045.050.0350	4.5	0.50	3.50	180	15.13	0.1829	18.0	2.25	2.60	4E
D.045.050.0450	4.5	0.50	4.50	180	17.18	0.1749	18.0	2.75	3.15	4E
D.045.050.0525	4.5	0.50	5.25	90	15.13	0.1281	18.0	3.13	2.60	4E
D.045.050.0575	4.5	0.50	5.75	270	17.18	0.1370	18.0	3.38	3.15	4E
D.045.050.0700	4.5	0.50	7.00	0	17.18	0.1125	18.0	4.00	3.15	4E
D.045.050.0775	4.5	0.50	7.75	270	15.13	0.0897	18.0	4.38	2.60	4E
D.045.050.0825	4.5	0.50	8.25	90	17.18	0.0955	18.0	4.63	3.15	4E
D.045.050.0950	4.5	0.50	9.50	180	17.18	0.0829	18.0	5.25	3.15	4E
D.045.050.1075	4.5	0.50	10.75	270	17.18	0.0733	18.0	5.88	3.15	4E
D.045.050.1200	4.5	0.50	12.00	0	15.13	0.0594	18.0	6.50	2.60	4E
D.046.040.0400	4.6	0.40	4.00	0	10.51	0.0584	18.4	2.00	2.80	4E
D.046.050.0700	4.6	0.50	7.00	0	21.10	0.1172	18.4	4.00	2.80	4E
D.046.063.0200	4.6	0.63	2.00	0	33.75	0.9926	18.4	1.89	3.00	4E
D.046.063.0325	4.6	0.63	3.25	90	33.75	0.6103	18.4	2.68	3.00	4E
D.046.063.0450	4.6	0.63	4.50	180	33.75	0.4412	18.4	3.47	3.00	4E
D.046.063.0575	4.6	0.63	5.75	270	33.75	0.3451	18.4	4.25	3.00	4E
D.046.063.0700	4.6	0.63	7.00	0	33.75	0.2834	18.4	5.04	3.00	4E
D.046.063.0825	4.6	0.63	8.25	90	33.75	0.2406	18.4	5.83	3.00	4E
D.046.063.0950	4.6	0.63	9.50	180	33.75	0.2088	18.4	6.62	3.00	4E
D.046.063.1075	4.6	0.63	10.75	270	33.75	0.1845	18.4	7.40	3.00	4E
D.047.055.0325	4.7	0.55	3.25	90	24.60	0.2733	18.8	2.34	2.80	4E
D.047.055.0700	4.7	0.55	7.00	0	24.60	0.1367	18.8	4.40	2.80	4E
D.047.055.0725	4.7	0.55	7.25	90	20.16	0.1343	18.8	4.54	3.15	4E
D.047.055.1075	4.7	0.55	10.75	270	24.60	0.0911	18.8	6.46	2.80	4E
D.048.050.0325	4.8	0.50	3.25	90	21.10	0.2344	19.2	2.13	2.80	4E
D.048.056.0700	4.8	0.56	7.00	0	34.80	0.1933	19.2	4.48	2.80	4E
D.048.056.0725	4.8	0.56	7.25	90	20.16	0.1413	19.2	4.62	3.23	4E
D.048.056.1075	4.8	0.56	10.75	270	34.80	0.1289	19.2	6.58	2.80	4E
D.049.036.0400	4.9	0.36	4.00	0	7.91	0.0439	19.6	1.80	2.80	4E
D.050.035.0350	5.0	0.35	3.50	180	5.70	0.0380	20.0	1.58	3.30	4E
D.050.035.0525	5.0	0.35	5.25	90	5.70	0.0266	20.0	2.19	3.30	4E
D.050.035.0775	5.0	0.35	7.75	270	5.70	0.0186	20.0	3.06	3.30	4E
D.050.035.1200	5.0	0.35	12.00	0	5.70	0.0123	20.0	4.55	3.30	4E
D.050.040.0575	5.0	0.40	5.75	270	10.51	0.0389	20.0	2.70	2.80	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.050.055.0350	5.0	0.55	3.50	180	20.16	0.2408	20.0	2.48	2.90	4E
D.050.055.0525	5.0	0.55	5.25	90	20.16	0.1686	20.0	3.44	2.90	4E
D.050.055.0775	5.0	0.55	7.75	270	20.16	0.1180	20.0	4.81	2.90	4E
D.050.055.1200	5.0	0.55	12.00	0	20.16	0.0782	20.0	7.15	2.90	4E
D.051.036.0575	5.1	0.36	5.75	270	7.91	0.0293	20.4	2.43	3.20	4E
D.052.036.0850	5.2	0.36	8.50	180	7.91	0.0220	20.8	3.42	3.20	4E
D.052.056.0325	5.2	0.56	3.25	90	34.80	0.3867	20.8	2.38	2.80	4E
D.053.040.0750	5.3	0.40	7.50	180	10.51	0.0292	21.2	3.40	2.80	4E
D.055.045.0500	5.5	0.45	5.00	0	15.82	0.0879	22.0	2.70	3.60	4E
D.055.050.0200	5.5	0.50	2.00	0	17.18	0.3152	22.0	1.50	4.00	4E
D.055.050.0325	5.5	0.50	3.25	90	17.18	0.1939	22.0	2.13	4.00	4E
D.055.050.0450	5.5	0.50	4.50	180	17.18	0.1400	22.0	2.75	4.00	4E
D.055.050.0575	5.5	0.50	5.75	270	17.18	0.1096	22.0	3.38	4.00	4E
D.055.050.0700	5.5	0.50	7.00	0	17.18	0.0900	22.0	4.00	4.00	4E
D.055.050.0825	5.5	0.50	8.25	90	17.18	0.0764	22.0	4.63	4.00	4E
D.055.050.0950	5.5	0.50	9.50	180	17.18	0.0664	22.0	5.25	4.00	4E
D.055.050.1075	5.5	0.50	10.75	270	17.18	0.0586	22.0	5.88	4.00	4E
D.056.040.0350	5.6	0.40	3.50	180	8.49	0.0580	22.4	1.80	3.70	4E
D.056.040.0525	5.6	0.40	5.25	90	8.49	0.0405	22.4	2.50	3.70	4E
D.056.040.0775	5.6	0.40	7.75	270	8.49	0.0283	22.4	3.50	3.70	4E
D.056.040.1200	5.6	0.40	12.00	0	8.49	0.0188	22.4	5.20	3.70	4E
D.056.060.0350	5.6	0.60	3.50	180	26.26	0.3036	22.4	2.70	3.30	4E
D.056.060.0525	5.6	0.60	5.25	90	26.26	0.2126	22.4	3.75	3.30	4E
D.056.060.0775	5.6	0.60	7.75	270	26.26	0.1488	22.4	5.25	3.30	4E
D.056.060.1200	5.6	0.60	12.00	0	26.26	0.0986	22.4	7.80	3.30	4E
D.056.063.0200	5.6	0.63	2.00	0	33.75	0.7941	22.4	1.89	3.90	4E
D.056.063.0325	5.6	0.63	3.25	90	33.75	0.4884	22.4	2.68	3.90	4E
D.056.063.0450	5.6	0.63	4.50	180	33.75	0.3530	22.4	3.47	3.90	4E
D.056.063.0575	5.6	0.63	5.75	270	33.75	0.2762	22.4	4.25	3.90	4E
D.056.063.0700	5.6	0.63	7.00	0	33.75	0.2268	22.4	5.04	3.90	4E
D.056.063.0825	5.6	0.63	8.25	90	33.75	0.1923	22.4	5.83	3.90	4E
D.056.063.0950	5.6	0.63	9.50	180	33.75	0.1663	22.4	6.62	3.90	4E
D.056.063.1075	5.6	0.63	10.75	270	33.75	0.1477	22.4	7.40	3.90	4E
D.056.065.1075	5.6	0.65	10.75	270	42.40	0.1570	22.4	7.64	3.60	4E
D.057.065.0700	5.7	0.65	7.00	0	42.40	0.2356	22.8	5.20	3.60	4E
D.057.070.0200	5.7	0.70	2.00	0	45.83	1.2092	22.8	2.10	3.80	4E
D.057.070.0325	5.7	0.70	3.25	90	45.83	0.7452	22.8	2.98	3.80	4E
D.057.070.0450	5.7	0.70	4.50	180	45.83	0.5379	22.8	3.85	3.80	4E
D.057.070.0575	5.7	0.70	5.75	270	45.83	0.4208	22.8	4.73	3.80	4E
D.057.070.0700	5.7	0.70	7.00	0	45.83	0.3456	22.8	5.60	3.80	4E
D.057.070.0825	5.7	0.70	8.25	90	45.83	0.2934	22.8	6.48	3.80	4E
D.057.070.0950	5.7	0.70	9.50	180	45.83	0.2546	22.8	7.35	3.80	4E
D.057.070.1075	5.7	0.70	10.75	270	45.83	0.2251	22.8	8.23	3.80	4E
D.059.045.0950	5.9	0.45	9.50	180	15.82	0.0439	23.6	4.73	4.00	4E
D.060.045.0850	6.0	0.45	8.50	180	13.22	0.0367	24.0	4.28	3.60	4E
D.060.065.0325	6.0	0.65	3.25	90	42.40	0.4711	24.0	2.76	3.60	4E
D.060.080.0200	6.0	0.80	2.00	0	67.41	1.9826	24.0	2.40	4.00	4E
D.060.080.0225	6.0	0.80	2.25	90	67.41	1.7647	24.0	2.60	4.00	4E
D.060.080.0250	6.0	0.80	2.50	180	67.41	1.5861	24.0	2.80	4.00	4E
D.060.080.0275	6.0	0.80	2.75	270	67.41	1.4435	24.0	3.00	4.00	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.060.080.0300	6.0	0.80	3.00	0	67.41	1.3244	24.0	3.20	4.00	4E
D.060.080.0325	6.0	0.80	3.25	90	67.41	1.2212	24.0	3.40	4.00	4E
D.060.080.0350	6.0	0.80	3.50	180	67.41	1.1348	24.0	3.60	4.00	4E
D.060.080.0375	6.0	0.80	3.75	270	67.41	1.0582	24.0	3.80	4.00	4E
D.060.080.0400	6.0	0.80	4.00	0	67.41	0.9928	24.0	4.00	4.00	4E
D.060.080.0525	6.0	0.80	5.25	90	67.41	0.7557	24.0	5.00	4.00	4E
D.060.080.0650	6.0	0.80	6.50	180	67.41	0.6106	24.0	6.00	4.00	4E
D.060.080.0775	6.0	0.80	7.75	270	67.41	0.5122	24.0	7.00	4.00	4E
D.062.045.0675	6.2	0.45	6.75	270	15.82	0.0586	24.8	3.49	4.00	4E
D.062.050.0500	6.2	0.50	5.00	0	21.10	0.1172	24.8	3.00	3.60	4E
D.062.070.1075	6.2	0.70	10.75	270	58.20	0.2156	24.8	8.23	3.60	4E
D.063.045.0350	6.3	0.45	3.50	180	11.50	0.0826	25.2	2.03	4.10	4E
D.063.045.0400	6.3	0.45	4.00	0	13.22	0.0734	25.2	2.25	4.00	4E
D.063.045.0525	6.3	0.45	5.25	90	11.50	0.0577	25.2	2.81	4.10	4E
D.063.045.0775	6.3	0.45	7.75	270	11.50	0.0404	25.2	3.94	4.10	4E
D.063.045.1200	6.3	0.45	12.00	0	11.50	0.0267	25.2	5.85	4.10	4E
D.063.055.0500	6.3	0.55	5.00	0	24.60	0.1367	25.2	3.30	4.00	4E
D.063.070.0350	6.3	0.70	3.50	180	41.51	0.5019	25.2	3.15	3.60	4E
D.063.070.0525	6.3	0.70	5.25	90	41.51	0.3515	25.2	4.38	3.60	4E
D.063.070.0700	6.3	0.70	7.00	0	58.20	0.3233	25.2	5.60	3.60	4E
D.063.070.0775	6.3	0.70	7.75	270	41.51	0.2461	25.2	6.13	3.60	4E
D.063.070.1200	6.3	0.70	12.00	0	41.51	0.1630	25.2	9.10	3.60	4E
D.064.050.1050	6.4	0.50	10.50	180	21.10	0.0586	25.6	5.75	4.00	4E
D.064.056.0775	6.4	0.56	7.75	270	34.80	0.1289	25.6	4.90	4.00	4E
D.065.050.0200	6.5	0.50	2.00	0	17.18	0.2627	26.0	1.50	5.00	4E
D.065.050.0325	6.5	0.50	3.25	90	17.18	0.1616	26.0	2.13	5.00	4E
D.065.050.0450	6.5	0.50	4.50	180	17.18	0.1167	26.0	2.75	5.00	4E
D.065.050.0575	6.5	0.50	5.75	270	17.18	0.0914	26.0	3.38	5.00	4E
D.065.050.0700	6.5	0.50	7.00	0	17.18	0.0751	26.0	4.00	5.00	4E
D.065.050.0825	6.5	0.50	8.25	90	17.18	0.0637	26.0	4.63	5.00	4E
D.065.050.0950	6.5	0.50	9.50	180	17.18	0.0553	26.0	5.25	5.00	4E
D.065.050.1075	6.5	0.50	10.75	270	17.18	0.0489	26.0	5.88	5.00	4E
D.066.045.0575	6.6	0.45	5.75	270	13.22	0.0490	26.4	3.04	4.00	4E
D.066.056.0500	6.6	0.56	5.00	0	34.80	0.1933	26.4	3.36	4.00	4E
D.066.063.0200	6.6	0.63	2.00	0	33.75	0.6618	26.4	1.89	4.80	4E
D.066.063.0325	6.6	0.63	3.25	90	33.75	0.4071	26.4	2.68	4.80	4E
D.066.063.0450	6.6	0.63	4.50	180	33.75	0.2942	26.4	3.47	4.80	4E
D.066.063.0575	6.6	0.63	5.75	270	33.75	0.2302	26.4	4.25	4.80	4E
D.066.063.0700	6.6	0.63	7.00	0	33.75	0.1888	26.4	5.04	4.80	4E
D.066.063.0825	6.6	0.63	8.25	90	33.75	0.1605	26.4	5.83	4.80	4E
D.066.063.0950	6.6	0.63	9.50	180	33.75	0.1393	26.4	6.62	4.80	4E
D.066.063.1075	6.6	0.63	10.75	270	33.75	0.1231	26.4	7.40	4.80	4E
D.067.070.0200	6.7	0.70	2.00	0	45.83	1.0095	26.8	2.10	4.70	4E
D.067.070.0450	6.7	0.70	4.50	180	45.83	0.4484	26.8	3.85	4.70	4E
D.067.070.0700	6.7	0.70	7.00	0	45.83	0.2882	26.8	5.60	4.70	4E
D.067.070.1075	6.7	0.70	10.75	270	45.83	0.1877	26.8	8.23	4.70	4E
D.067.080.1075	6.7	0.80	10.75	270	92.70	0.3433	26.8	9.40	4.00	4E
D.068.050.0675	6.8	0.50	6.75	270	21.10	0.0781	27.2	3.88	4.40	4E
D.068.070.0325	6.8	0.70	3.25	90	58.20	0.6467	27.2	2.98	4.00	4E
D.069.055.0950	6.9	0.55	9.50	180	24.60	0.0683	27.6	5.78	4.80	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.069.056.0950	6.9	0.56	9.50	180	34.80	0.0967	27.6	5.88	4.40	4E
D.069.075.0700	6.9	0.75	7.00	0	70.60	0.3922	27.6	6.00	4.40	4E
D.069.075.1075	6.9	0.75	10.75	270	70.60	0.2615	27.6	8.81	4.40	4E
D.069.080.0700	6.9	0.80	7.00	0	92.70	0.5150	27.6	6.40	4.00	4E
D.070.050.0350	7.0	0.50	3.50	180	15.78	0.1133	28.0	2.25	4.60	4E
D.070.050.0525	7.0	0.50	5.25	90	15.78	0.0792	28.0	3.13	4.60	4E
D.070.050.0775	7.0	0.50	7.75	270	15.78	0.0554	28.0	4.38	4.60	4E
D.070.050.1200	7.0	0.50	12.00	0	15.78	0.0366	28.0	6.50	4.60	4E
D.070.080.0350	7.0	0.80	3.50	180	58.58	0.7730	28.0	3.60	4.00	4E
D.070.080.0525	7.0	0.80	5.25	90	58.58	0.5414	28.0	5.00	4.00	4E
D.070.080.0775	7.0	0.80	7.75	270	58.58	0.3791	28.0	7.00	4.00	4E
D.070.080.1200	7.0	0.80	12.00	0	58.58	0.2511	28.0	10.40	4.00	4E
D.071.075.0325	7.1	0.75	3.25	90	70.60	0.7844	28.4	3.19	4.40	4E
D.072.055.0675	7.2	0.55	6.75	270	24.60	0.0911	28.8	4.26	4.80	4E
D.073.080.0325	7.3	0.80	3.25	90	92.70	1.0300	29.2	3.40	4.40	4E
D.075.100.0200	7.5	1.00	2.00	0	127.82	3.8733	30.0	3.00	5.00	4I
D.075.100.0225	7.5	1.00	2.25	90	127.82	3.4453	30.0	3.25	5.00	4I
D.075.100.0250	7.5	1.00	2.50	180	127.82	3.1024	30.0	3.50	5.00	4I
D.075.100.0275	7.5	1.00	2.75	270	127.82	2.8216	30.0	3.75	5.00	4I
D.075.100.0300	7.5	1.00	3.00	0	127.82	2.5822	30.0	4.00	5.00	4I
D.075.100.0325	7.5	1.00	3.25	90	127.82	2.3847	30.0	4.25	5.00	4I
D.075.100.0350	7.5	1.00	3.50	180	127.82	2.2153	30.0	4.50	5.00	4I
D.075.100.0375	7.5	1.00	3.75	270	127.82	2.0683	30.0	4.75	5.00	4I
D.075.100.0400	7.5	1.00	4.00	0	127.82	1.9367	30.0	5.00	5.00	4I
D.075.100.0525	7.5	1.00	5.25	90	127.82	1.4760	30.0	6.25	5.00	4I
D.075.100.0650	7.5	1.00	6.50	180	127.82	1.1924	30.0	7.50	5.00	4I
D.075.100.0775	7.5	1.00	7.75	270	127.82	1.0002	30.0	8.75	5.00	4I
D.076.063.0200	7.6	0.63	2.00	0	33.75	0.5672	30.4	1.89	5.70	4E
D.076.063.0325	7.6	0.63	3.25	90	33.75	0.3490	30.4	2.68	5.70	4E
D.076.063.0450	7.6	0.63	4.50	180	33.75	0.2522	30.4	3.47	5.70	4E
D.076.063.0575	7.6	0.63	5.75	270	33.75	0.1974	30.4	4.25	5.70	4E
D.076.063.0700	7.6	0.63	7.00	0	33.75	0.1621	30.4	5.04	5.70	4E
D.076.063.0825	7.6	0.63	8.25	90	33.75	0.1375	30.4	5.83	5.70	4E
D.076.063.0950	7.6	0.63	9.50	180	33.75	0.1195	30.4	6.62	5.70	4E
D.076.063.1075	7.6	0.63	10.75	270	33.75	0.1056	30.4	7.40	5.70	4E
D.076.080.0200	7.6	0.80	2.00	0	67.41	1.5182	30.4	2.40	5.40	4E
D.076.080.0225	7.6	0.80	2.25	90	67.41	1.3509	30.4	2.60	5.40	4E
D.076.080.0250	7.6	0.80	2.50	180	67.41	1.2146	30.4	2.80	5.40	4E
D.076.080.0275	7.6	0.80	2.75	270	67.41	1.1051	30.4	3.00	5.40	4E
D.076.080.0300	7.6	0.80	3.00	0	67.41	1.0122	30.4	3.20	5.40	4E
D.076.080.0325	7.6	0.80	3.25	90	67.41	0.9350	30.4	3.40	5.40	4E
D.076.080.0350	7.6	0.80	3.50	180	67.41	0.8676	30.4	3.60	5.40	4E
D.076.080.0375	7.6	0.80	3.75	270	67.41	0.8102	30.4	3.80	5.40	4E
D.076.080.0400	7.6	0.80	4.00	0	67.41	0.7591	30.4	4.00	5.40	4E
D.076.080.0525	7.6	0.80	5.25	90	67.41	0.5786	30.4	5.00	5.40	4E
D.076.080.0650	7.6	0.80	6.50	180	67.41	0.4672	30.4	6.00	5.40	4E
D.076.080.0775	7.6	0.80	7.75	270	67.41	0.3919	30.4	7.00	5.40	4E
D.077.065.0500	7.7	0.65	5.00	0	42.40	0.2356	30.8	3.90	5.20	4E
D.077.070.0200	7.7	0.70	2.00	0	45.83	0.8647	30.8	2.10	5.60	4E
D.077.070.0325	7.7	0.70	3.25	90	45.83	0.5323	30.8	2.98	5.60	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.077.070.0450	7.7	0.70	4.50	180	45.83	0.3845	30.8	3.85	5.60	4E
D.077.070.0575	7.7	0.70	5.75	270	45.83	0.3007	30.8	4.73	5.60	4E
D.077.070.0700	7.7	0.70	7.00	0	45.83	0.2471	30.8	5.60	5.60	4E
D.077.070.0825	7.7	0.70	8.25	90	45.83	0.2097	30.8	6.48	5.60	4E
D.077.070.0950	7.7	0.70	9.50	180	45.83	0.1821	30.8	7.35	5.60	4E
D.077.070.1075	7.7	0.70	10.75	270	45.83	0.1609	30.8	8.23	5.60	4E
D.077.090.0800	7.7	0.90	8.00	0	113.00	0.6278	30.8	8.10	4.80	4I
D.078.100.0425	7.8	1.00	4.25	90	155.40	1.7267	31.2	5.25	4.80	4I
D.079.090.1075	7.9	0.90	10.75	270	113.00	0.4185	31.6	10.58	4.80	4I
D.080.055.0350	8.0	0.55	3.50	180	21.06	0.1448	32.0	2.48	5.30	4E
D.080.055.0525	8.0	0.55	5.25	90	21.06	0.1012	32.0	3.44	5.30	4E
D.080.055.0775	8.0	0.55	7.75	270	21.06	0.0707	32.0	4.81	5.30	4E
D.080.055.1200	8.0	0.55	12.00	0	21.06	0.0468	32.0	7.15	5.30	4E
D.080.090.0325	8.0	0.90	3.25	90	113.00	1.2556	32.0	3.83	4.80	4I
D.080.090.0350	8.0	0.90	3.50	180	83.58	1.0815	32.0	4.05	4.60	4I
D.080.090.0525	8.0	0.90	5.25	90	83.58	0.7574	32.0	5.63	4.60	4I
D.080.090.0775	8.0	0.90	7.75	270	83.58	0.5303	32.0	7.88	4.60	4I
D.080.090.1200	8.0	0.90	12.00	0	83.58	0.3513	32.0	11.70	4.60	4I
D.082.065.0950	8.2	0.65	9.50	180	42.40	0.1178	32.8	6.83	5.50	4E
D.084.070.0775	8.4	0.70	7.75	270	58.20	0.2156	33.6	6.13	5.20	4E
D.086.065.0675	8.6	0.65	6.75	270	42.40	0.1570	34.4	5.04	5.50	4E
D.086.070.0500	8.6	0.70	5.00	0	58.20	0.3233	34.4	4.20	5.20	4E
D.087.070.0200	8.7	0.70	2.00	0	45.83	0.7563	34.8	2.10	6.50	4E
D.087.070.0325	8.7	0.70	3.25	90	45.83	0.4658	34.8	2.98	6.50	4E
D.087.070.0450	8.7	0.70	4.50	180	45.83	0.3362	34.8	3.85	6.50	4E
D.087.070.0575	8.7	0.70	5.75	270	45.83	0.2632	34.8	4.73	6.50	4E
D.087.070.0700	8.7	0.70	7.00	0	45.83	0.2162	34.8	5.60	6.50	4E
D.087.070.0825	8.7	0.70	8.25	90	45.83	0.1835	34.8	6.48	6.50	4E
D.087.070.0950	8.7	0.70	9.50	180	45.83	0.1593	34.8	7.35	6.50	4E
D.087.070.1075	8.7	0.70	10.75	270	45.83	0.1408	34.8	8.23	6.50	4E
D.088.065.0700	8.8	0.65	7.00	0	26.26	0.1384	35.2	5.20	6.46	4E
D.088.080.0200	8.8	0.80	2.00	0	67.41	1.2914	35.2	2.40	6.50	4E
D.088.080.0225	8.8	0.80	2.25	90	67.41	1.1484	35.2	2.60	6.50	4E
D.088.080.0250	8.8	0.80	2.50	180	67.41	1.0323	35.2	2.80	6.50	4E
D.088.080.0275	8.8	0.80	2.75	270	67.41	0.9389	35.2	3.00	6.50	4E
D.088.080.0300	8.8	0.80	3.00	0	67.41	0.8609	35.2	3.20	6.50	4E
D.088.080.0325	8.8	0.80	3.25	90	67.41	0.7940	35.2	3.40	6.50	4E
D.088.080.0350	8.8	0.80	3.50	180	67.41	0.7375	35.2	3.60	6.50	4E
D.088.080.0375	8.8	0.80	3.75	270	67.41	0.6886	35.2	3.80	6.50	4E
D.088.080.0400	8.8	0.80	4.00	0	67.41	0.6457	35.2	4.00	6.50	4E
D.088.080.0525	8.8	0.80	5.25	90	67.41	0.4917	35.2	5.00	6.50	4E
D.088.080.0650	8.8	0.80	6.50	180	67.41	0.3972	35.2	6.00	6.50	4E
D.088.080.0775	8.8	0.80	7.75	270	67.41	0.3332	35.2	7.00	6.50	4E
D.088.100.0800	8.8	1.00	8.00	0	155.40	0.8633	35.2	9.00	5.50	4I
D.089.130.3075	8.9	1.30	30.75	270	248.00	0.5950	35.6	41.28	5.20	4I
D.090.060.0350	9.0	0.60	3.50	180	27.40	0.1819	36.0	2.70	6.00	4E
D.090.060.0525	9.0	0.60	5.25	90	27.40	0.1271	36.0	3.75	6.00	4E
D.090.060.0775	9.0	0.60	7.75	270	27.40	0.0889	36.0	5.25	6.00	4E
D.090.060.1200	9.0	0.60	12.00	0	27.40	0.0588	36.0	7.80	6.00	4E
D.090.070.0950	9.0	0.70	9.50	180	58.20	0.1617	36.0	7.35	5.50	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.090.080.0775	9.0	0.80	7.75	270	92.70	0.3433	36.0	7.00	5.50	4E
D.090.100.0350	9.0	1.00	3.50	180	114.84	1.4633	36.0	4.50	5.20	4I
D.090.100.0525	9.0	1.00	5.25	90	114.84	1.0247	36.0	6.25	5.20	4I
D.090.100.0775	9.0	1.00	7.75	270	114.84	0.7175	36.0	8.75	5.20	4I
D.090.100.1175	9.0	1.00	11.75	270	134.50	0.4981	36.0	12.75	5.50	4I
D.090.100.1200	9.0	1.00	12.00	0	114.84	0.4752	36.0	13.00	5.20	4I
D.091.100.1175	9.1	1.00	11.75	270	155.40	0.5756	36.4	12.75	5.50	4I
D.091.112.0425	9.1	1.12	4.25	90	226.00	2.5111	36.4	5.88	5.20	4I
D.093.080.0500	9.3	0.80	5.00	0	92.70	0.5150	37.2	4.80	5.50	4E
D.094.100.0700	9.4	1.00	7.00	0	134.50	0.7472	37.6	8.00	5.50	4I
D.095.100.0200	9.5	1.00	2.00	0	127.82	2.9657	38.0	3.00	6.70	4I
D.095.100.0225	9.5	1.00	2.25	90	127.82	2.6355	38.0	3.25	6.70	4I
D.095.100.0250	9.5	1.00	2.50	180	127.82	2.3714	38.0	3.50	6.70	4I
D.095.100.0275	9.5	1.00	2.75	270	127.82	2.1555	38.0	3.75	6.70	4I
D.095.100.0300	9.5	1.00	3.00	0	127.82	1.9756	38.0	4.00	6.70	4I
D.095.100.0325	9.5	1.00	3.25	90	127.82	1.8260	38.0	4.25	6.70	4I
D.095.100.0350	9.5	1.00	3.50	180	127.82	1.6952	38.0	4.50	6.70	4I
D.095.100.0375	9.5	1.00	3.75	270	127.82	1.5819	38.0	4.75	6.70	4I
D.095.100.0400	9.5	1.00	4.00	0	127.82	1.4828	38.0	5.00	6.70	4I
D.095.100.0525	9.5	1.00	5.25	90	127.82	1.1302	38.0	6.25	6.70	4I
D.095.100.0650	9.5	1.00	6.50	180	127.82	0.9123	38.0	7.50	6.70	4I
D.095.100.0775	9.5	1.00	7.75	270	127.82	0.7654	38.0	8.75	6.70	4I
D.095.120.0425	9.5	1.20	4.25	90	282.00	3.1333	38.0	6.30	5.50	4I
D.096.075.0775	9.6	0.75	7.75	270	70.60	0.2615	38.4	6.56	6.40	4E
D.096.112.0800	9.6	1.12	8.00	0	226.00	1.2556	38.4	10.08	5.50	4I
D.097.080.0950	9.7	0.80	9.50	180	92.70	0.2575	38.8	8.40	6.00	4E
D.097.112.1175	9.7	1.12	11.75	270	226.00	0.8370	38.8	14.28	5.90	4I
D.098.100.0325	9.8	1.00	3.25	90	134.50	1.4944	39.2	4.25	5.90	4I
D.098.140.0575	9.8	1.40	5.75	270	358.00	4.2060	39.2	9.45	5.70	4J
D.100.070.0350	10.0	0.70	3.50	180	43.36	0.3042	40.0	3.15	6.60	4E
D.100.070.0525	10.0	0.70	5.25	90	43.36	0.2126	40.0	4.38	6.60	4E
D.100.070.0775	10.0	0.70	7.75	270	43.36	0.1487	40.0	6.13	6.60	4E
D.100.070.1200	10.0	0.70	12.00	0	43.36	0.0984	40.0	9.10	6.60	4E
D.100.075.0500	10.0	0.75	5.00	0	70.60	0.3922	40.0	4.50	6.40	4E
D.100.110.0350	10.0	1.10	3.50	180	144.81	1.9262	40.0	4.95	5.80	4I
D.100.110.0525	10.0	1.10	5.25	90	144.81	1.3487	40.0	6.88	5.80	4I
D.100.110.0775	10.0	1.10	7.75	270	144.81	0.9443	40.0	9.63	5.80	4I
D.100.110.1200	10.0	1.10	12.00	0	144.81	0.6255	40.0	14.30	5.80	4I
D.103.120.0800	10.3	1.20	8.00	0	282.00	1.5667	41.2	10.80	6.40	4I
D.104.075.0950	10.4	0.75	9.50	180	70.60	0.1961	41.6	7.88	6.40	4E
D.104.130.0425	10.4	1.30	4.25	90	328.00	3.6444	41.6	6.83	5.90	4I
D.106.120.1175	10.6	1.20	11.75	270	282.00	1.0444	42.4	15.30	6.40	4I
D.108.080.0200	10.8	0.80	2.00	0	67.41	1.0323	43.2	2.40	8.30	4E
D.108.080.0225	10.8	0.80	2.25	90	67.41	0.9184	43.2	2.60	8.30	4E
D.108.080.0250	10.8	0.80	2.50	180	67.41	0.8261	43.2	2.80	8.30	4E
D.108.080.0275	10.8	0.80	2.75	270	67.41	0.7515	43.2	3.00	8.30	4E
D.108.080.0300	10.8	0.80	3.00	0	67.41	0.6886	43.2	3.20	8.30	4E
D.108.080.0325	10.8	0.80	3.25	90	67.41	0.6359	43.2	3.40	8.30	4E
D.108.080.0350	10.8	0.80	3.50	180	67.41	0.5903	43.2	3.60	8.30	4E
D.108.080.0375	10.8	0.80	3.75	270	67.41	0.5507	43.2	3.80	8.30	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.108.080.0400	10.8	0.80	4.00	0	67.41	0.5166	43.2	4.00	8.30	4E
D.108.080.0525	10.8	0.80	5.25	90	67.41	0.3935	43.2	5.00	8.30	4E
D.108.080.0650	10.8	0.80	6.50	180	67.41	0.3178	43.2	6.00	8.30	4E
D.108.080.0775	10.8	0.80	7.75	270	67.41	0.2665	43.2	7.00	8.30	4E
D.108.130.0675	10.8	1.30	6.75	270	237.00	2.3370	43.2	10.08	6.69	4I
D.109.130.0800	10.9	1.30	8.00	0	328.00	1.8222	43.6	11.70	6.40	4I
D.110.080.0350	11.0	0.80	3.50	180	61.26	0.4730	44.0	3.60	7.30	4E
D.110.080.0525	11.0	0.80	5.25	90	61.26	0.3306	44.0	5.00	7.30	4E
D.110.080.0775	11.0	0.80	7.75	270	61.26	0.2312	44.0	7.00	7.30	4E
D.110.080.1200	11.0	0.80	12.00	0	61.26	0.1530	44.0	10.40	7.30	4E
D.110.090.0775	11.0	0.90	7.75	270	113.00	0.4185	44.0	7.88	7.10	4I
D.110.100.0200	11.0	1.00	2.00	0	127.82	2.5211	44.0	3.00	8.10	4I
D.110.100.0225	11.0	1.00	2.25	90	127.82	2.2425	44.0	3.25	8.10	4I
D.110.100.0250	11.0	1.00	2.50	180	127.82	2.0161	44.0	3.50	8.10	4I
D.110.100.0275	11.0	1.00	2.75	270	127.82	1.8339	44.0	3.75	8.10	4I
D.110.100.0300	11.0	1.00	3.00	0	127.82	1.6818	44.0	4.00	8.10	4I
D.110.100.0325	11.0	1.00	3.25	90	127.82	1.5512	44.0	4.25	8.10	4I
D.110.100.0350	11.0	1.00	3.50	180	127.82	1.4410	44.0	4.50	8.10	4I
D.110.100.0375	11.0	1.00	3.75	270	127.82	1.3441	44.0	4.75	8.10	4I
D.110.100.0400	11.0	1.00	4.00	0	127.82	1.2606	44.0	5.00	8.10	4I
D.110.100.0525	11.0	1.00	5.25	90	127.82	0.9603	44.0	6.25	8.10	4I
D.110.100.0650	11.0	1.00	6.50	180	127.82	0.7756	44.0	7.50	8.10	4I
D.110.100.0775	11.0	1.00	7.75	270	127.82	0.6505	44.0	8.75	8.10	4I
D.110.125.0350	11.0	1.25	3.50	180	211.62	2.9301	44.0	5.63	6.30	4I
D.110.125.0525	11.0	1.25	5.25	90	211.62	2.0521	44.0	7.81	6.30	4I
D.110.125.0775	11.0	1.25	7.75	270	211.62	1.4359	44.0	10.94	6.30	4I
D.110.125.1200	11.0	1.25	12.00	0	211.62	0.9519	44.0	16.25	6.30	4I
D.112.130.1275	11.2	1.30	12.75	270	328.00	1.2148	44.8	17.88	6.80	4I
D.114.090.0500	11.4	0.90	5.00	0	113.00	0.6278	45.6	5.40	7.10	4I
D.118.125.0200	11.8	1.25	2.00	0	242.94	5.8540	47.2	3.75	8.30	4I
D.118.125.0225	11.8	1.25	2.25	90	242.94	5.2133	47.2	4.06	8.30	4I
D.118.125.0250	11.8	1.25	2.50	180	242.94	4.6900	47.2	4.38	8.30	4I
D.118.125.0275	11.8	1.25	2.75	270	242.94	4.2621	47.2	4.69	8.30	4I
D.118.125.0300	11.8	1.25	3.00	0	242.94	3.9058	47.2	5.00	8.30	4I
D.118.125.0325	11.8	1.25	3.25	90	242.94	3.6045	47.2	5.31	8.30	4I
D.118.125.0350	11.8	1.25	3.50	180	242.94	3.3509	47.2	5.63	8.30	4I
D.118.125.0375	11.8	1.25	3.75	270	242.94	3.1266	47.2	5.94	8.30	4I
D.118.125.0400	11.8	1.25	4.00	0	242.94	2.9305	47.2	6.25	8.30	4I
D.118.125.0525	11.8	1.25	5.25	90	242.94	2.2329	47.2	7.81	8.30	4I
D.118.125.0650	11.8	1.25	6.50	180	242.94	1.8036	47.2	9.38	8.30	4I
D.118.125.0775	11.8	1.25	7.75	270	242.94	1.5127	47.2	10.94	8.30	4I
D.120.090.0950	12.0	0.90	9.50	180	113.00	0.3139	48.0	9.45	7.90	4I
D.121.100.0775	12.1	1.00	7.75	270	134.50	0.4981	48.4	8.75	7.90	4I
D.121.160.0200	12.1	1.60	2.00	0	489.79	15.7489	48.4	4.80	8.00	4J
D.121.160.0225	12.1	1.60	2.25	90	489.79	13.9940	48.4	5.20	8.00	4J
D.121.160.0250	12.1	1.60	2.50	180	489.79	12.5910	48.4	5.60	8.00	4J
D.121.160.0275	12.1	1.60	2.75	270	489.79	11.4437	48.4	6.00	8.00	4J
D.121.160.0300	12.1	1.60	3.00	0	489.79	10.4880	48.4	6.40	8.00	4J
D.121.160.0325	12.1	1.60	3.25	90	489.79	9.6796	48.4	6.80	8.00	4J
D.121.160.0350	12.1	1.60	3.50	180	489.79	8.9870	48.4	7.20	8.00	4J

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.121.160.0375	12.1	1.60	3.75	270	489.79	8.3868	48.4	7.60	8.00	4J
D.121.160.0400	12.1	1.60	4.00	0	489.79	7.8618	48.4	8.00	8.00	4J
D.121.160.0525	12.1	1.60	5.25	90	489.79	5.9877	48.4	10.00	8.00	4J
D.121.160.0650	12.1	1.60	6.50	180	489.79	4.8398	48.4	12.00	8.00	4J
D.121.160.0775	12.1	1.60	7.75	270	489.79	4.0579	48.4	14.00	8.00	4J
D.123.140.0425	12.3	1.40	4.25	90	370.00	4.1111	49.2	7.35	7.50	4J
D.124.100.0500	12.4	1.00	5.00	0	134.50	0.7472	49.6	6.00	8.10	4I
D.125.090.0350	12.5	0.90	3.50	180	87.29	0.6663	50.0	4.05	8.30	4I
D.125.090.0525	12.5	0.90	5.25	90	87.29	0.4657	50.0	5.63	8.30	4I
D.125.090.0775	12.5	0.90	7.75	270	87.29	0.3256	50.0	7.88	8.30	4I
D.125.090.1200	12.5	0.90	12.00	0	87.29	0.2155	50.0	11.70	8.30	4I
D.125.140.0350	12.5	1.40	3.50	180	297.87	4.0509	50.0	6.30	7.20	4J
D.125.140.0525	12.5	1.40	5.25	90	297.87	2.8368	50.0	8.75	7.20	4J
D.125.140.0775	12.5	1.40	7.75	270	297.87	1.9863	50.0	12.25	7.20	4J
D.125.140.1200	12.5	1.40	12.00	0	297.87	1.3157	50.0	18.20	7.20	4J
D.127.150.0425	12.7	1.50	4.25	90	475.00	5.2778	50.8	7.88	7.50	4J
D.127.150.0525	12.7	1.50	5.25	90	395.00	4.2700	50.8	9.38	7.84	4J
D.129.100.1050	12.9	1.00	10.50	180	155.40	0.4317	51.6	11.50	8.70	4I
D.129.140.0800	12.9	1.40	8.00	0	370.00	2.0556	51.6	12.60	7.90	4J
D.130.100.0775	13.0	1.00	7.75	270	155.40	0.5756	52.0	8.75	8.70	4I
D.131.100.1050	13.1	1.00	10.50	180	134.50	0.3736	52.4	11.50	8.30	4I
D.131.140.1175	13.1	1.40	11.75	270	370.00	1.3704	52.4	17.85	7.90	4J
D.132.100.0500	13.2	1.00	5.00	0	155.40	0.8633	52.8	6.00	8.70	4I
D.134.150.0800	13.4	1.50	8.00	0	475.00	2.6389	53.6	13.50	8.30	4J
D.135.100.0200	13.5	1.00	2.00	0	127.82	2.0161	54.0	3.00	10.30	4I
D.135.100.0225	13.5	1.00	2.25	90	127.82	1.7927	54.0	3.25	10.30	4I
D.135.100.0250	13.5	1.00	2.50	180	127.82	1.6139	54.0	3.50	10.30	4I
D.135.100.0275	13.5	1.00	2.75	270	127.82	1.4675	54.0	3.75	10.30	4I
D.135.100.0300	13.5	1.00	3.00	0	127.82	1.3455	54.0	4.00	10.30	4I
D.135.100.0325	13.5	1.00	3.25	90	127.82	1.2410	54.0	4.25	10.30	4I
D.135.100.0350	13.5	1.00	3.50	180	127.82	1.1526	54.0	4.50	10.30	4I
D.135.100.0375	13.5	1.00	3.75	270	127.82	1.0752	54.0	4.75	10.30	4I
D.135.100.0400	13.5	1.00	4.00	0	127.82	1.0088	54.0	5.00	10.30	4I
D.135.100.0525	13.5	1.00	5.25	90	127.82	0.7686	54.0	6.25	10.30	4I
D.135.100.0650	13.5	1.00	6.50	180	127.82	0.6208	54.0	7.50	10.30	4I
D.135.100.0775	13.5	1.00	7.75	270	127.82	0.5207	54.0	8.75	10.30	4I
D.136.150.1175	13.6	1.50	11.75	270	399.00	1.7580	54.4	19.13	8.59	4J
D.136.150.1275	13.6	1.50	12.75	270	475.00	1.7593	54.4	20.63	8.30	4J
D.138.125.0200	13.8	1.25	2.00	0	242.94	4.8950	55.2	3.75	10.10	4I
D.138.125.0225	13.8	1.25	2.25	90	242.94	4.3773	55.2	4.06	10.10	4I
D.138.125.0250	13.8	1.25	2.50	180	242.94	3.9374	55.2	4.38	10.10	4I
D.138.125.0275	13.8	1.25	2.75	270	242.94	3.5832	55.2	4.69	10.10	4I
D.138.125.0300	13.8	1.25	3.00	0	242.94	3.2830	55.2	5.00	10.10	4I
D.138.125.0325	13.8	1.25	3.25	90	242.94	3.0292	55.2	5.31	10.10	4I
D.138.125.0350	13.8	1.25	3.50	180	242.94	2.8151	55.2	5.63	10.10	4I
D.138.125.0375	13.8	1.25	3.75	270	242.94	2.6264	55.2	5.94	10.10	4I
D.138.125.0400	13.8	1.25	4.00	0	242.94	2.4614	55.2	6.25	10.10	4I
D.138.125.0525	13.8	1.25	5.25	90	242.94	1.8760	55.2	7.81	10.10	4I
D.138.125.0650	13.8	1.25	6.50	180	242.94	1.5155	55.2	9.38	10.10	4I
D.138.125.0775	13.8	1.25	7.75	270	242.94	1.2706	55.2	10.94	10.10	4I

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.139.112.1050	13.9	1.12	10.50	180	226.00	0.6278	55.6	12.88	9.10	4I
D.140.100.0350	14.0	1.00	3.50	180	119.80	0.9063	56.0	4.50	9.30	4I
D.140.100.0525	14.0	1.00	5.25	90	119.80	0.6334	56.0	6.25	9.30	4I
D.140.100.0775	14.0	1.00	7.75	270	119.80	0.4429	56.0	8.75	9.30	4I
D.140.100.1200	14.0	1.00	12.00	0	119.80	0.2931	56.0	13.00	9.30	4I
D.140.160.0350	14.0	1.60	3.50	180	420.79	6.1839	56.0	7.20	8.00	4J
D.140.160.0525	14.0	1.60	5.25	90	420.79	4.3309	56.0	10.00	8.00	4J
D.140.160.0775	14.0	1.60	7.75	270	420.79	3.0326	56.0	14.00	8.00	4J
D.140.160.1200	14.0	1.60	12.00	0	420.79	2.0090	56.0	20.80	8.00	4J
D.141.112.0775	14.1	1.12	7.75	270	226.00	0.8370	56.4	9.80	9.10	4I
D.141.130.0600	14.1	1.30	6.00	0	328.00	1.8222	56.4	9.10	8.70	4I
D.142.160.0425	14.2	1.60	4.25	90	582.00	6.4667	56.8	8.40	8.70	4J
D.145.130.0875	14.5	1.30	8.75	270	328.00	1.2148	58.0	12.68	9.10	4I
D.146.112.0500	14.6	1.12	5.00	0	226.00	1.2556	58.4	6.72	9.10	4I
D.150.160.0800	15.0	1.60	8.00	0	582.00	3.2333	60.0	14.40	9.10	4J
D.150.200.0200	15.0	2.00	2.00	0	912.63	31.0418	60.0	6.00	9.90	4K
D.150.200.0225	15.0	2.00	2.25	90	912.63	27.5719	60.0	6.50	9.90	4K
D.150.200.0250	15.0	2.00	2.50	180	912.63	24.7997	60.0	7.00	9.90	4K
D.150.200.0275	15.0	2.00	2.75	270	912.63	22.5341	60.0	7.50	9.90	4K
D.150.200.0300	15.0	2.00	3.00	0	912.63	20.6946	60.0	8.00	9.90	4K
D.150.200.0325	15.0	2.00	3.25	90	912.63	19.0927	60.0	8.50	9.90	4K
D.150.200.0350	15.0	2.00	3.50	180	912.63	17.7210	60.0	9.00	9.90	4K
D.150.200.0375	15.0	2.00	3.75	270	912.63	16.5332	60.0	9.50	9.90	4K
D.150.200.0400	15.0	2.00	4.00	0	912.63	15.4946	60.0	10.00	9.90	4K
D.150.200.0525	15.0	2.00	5.25	90	912.63	11.8063	60.0	12.50	9.90	4K
D.150.200.0650	15.0	2.00	6.50	180	912.63	9.5463	60.0	15.00	9.90	4K
D.150.200.0775	15.0	2.00	7.75	270	912.63	8.0055	60.0	17.50	9.90	4K
D.150.250.0200	15.0	2.50	2.00	0	1696.59	78.5458	60.0	7.50	9.00	4L
D.150.250.0325	15.0	2.50	3.25	90	1696.59	48.4740	60.0	10.63	9.00	4L
D.150.250.0450	15.0	2.50	4.50	180	1696.59	34.9812	60.0	13.75	9.00	4L
D.150.250.0575	15.0	2.50	5.75	270	1696.59	27.3644	60.0	16.88	9.00	4L
D.150.250.0700	15.0	2.50	7.00	0	1696.59	22.4714	60.0	20.00	9.00	4L
D.150.250.0825	15.0	2.50	8.25	90	1696.59	19.0628	60.0	23.13	9.00	4L
D.150.250.0950	15.0	2.50	9.50	180	1696.59	16.5683	60.0	26.25	9.00	4L
D.150.250.1075	15.0	2.50	10.75	270	1696.59	14.6384	60.0	29.38	9.00	4L
D.151.120.1050	15.1	1.20	10.50	180	282.00	0.7833	60.4	13.80	10.30	4I
D.151.160.0200	15.1	1.60	2.00	0	489.79	12.2448	60.4	4.80	10.70	4J
D.151.160.0225	15.1	1.60	2.25	90	489.79	10.8842	60.4	5.20	10.70	4J
D.151.160.0250	15.1	1.60	2.50	180	489.79	9.7958	60.4	5.60	10.70	4J
D.151.160.0275	15.1	1.60	2.75	270	489.79	8.9053	60.4	6.00	10.70	4J
D.151.160.0300	15.1	1.60	3.00	0	489.79	8.1632	60.4	6.40	10.70	4J
D.151.160.0325	15.1	1.60	3.25	90	489.79	7.5352	60.4	6.80	10.70	4J
D.151.160.0350	15.1	1.60	3.50	180	489.79	6.9970	60.4	7.20	10.70	4J
D.151.160.0375	15.1	1.60	3.75	270	489.79	6.5305	60.4	7.60	10.70	4J
D.151.160.0400	15.1	1.60	4.00	0	489.79	6.1224	60.4	8.00	10.70	4J
D.151.160.0525	15.1	1.60	5.25	90	489.79	4.6602	60.4	10.00	10.70	4J
D.151.160.0650	15.1	1.60	6.50	180	489.79	3.7647	60.4	12.00	10.70	4J
D.151.160.0775	15.1	1.60	7.75	270	489.79	3.1579	60.4	14.00	10.70	4J
D.151.180.0425	15.1	1.80	4.25	90	791.00	8.7889	60.4	9.45	9.10	4J
D.152.120.0775	15.2	1.20	7.75	270	282.00	1.0444	60.8	10.50	10.30	4I

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.152.160.1175	15.2	1.60	11.75	270	582.00	2.1556	60.8	20.40	9.50	4J
D.157.120.0500	15.7	1.20	5.00	0	282.00	1.5667	62.8	7.20	10.30	4I
D.159.180.0800	15.9	1.80	8.00	0	791.00	4.3944	63.6	16.20	9.90	4J
D.160.110.0350	16.0	1.10	3.50	180	151.29	1.1581	64.0	4.95	10.70	4I
D.160.110.0525	16.0	1.10	5.25	90	151.29	0.8093	64.0	6.88	10.70	4I
D.160.110.0775	16.0	1.10	7.75	270	151.29	0.6669	64.0	9.63	10.70	4I
D.160.110.1200	16.0	1.10	12.00	0	151.29	0.3744	64.0	14.30	10.70	4I
D.160.130.1150	16.0	1.30	11.50	180	328.00	0.9111	64.0	16.25	10.30	4I
D.160.180.0350	16.0	1.80	3.50	180	600.36	8.6523	64.0	8.10	9.20	4J
D.160.180.0525	16.0	1.80	5.25	90	600.36	8.0592	64.0	11.25	9.20	4J
D.160.180.0775	16.0	1.80	7.75	270	600.36	4.2427	64.0	15.75	9.20	4J
D.160.180.1200	16.0	1.80	12.00	0	600.36	2.8104	64.0	23.40	9.20	4J
D.161.190.0425	16.1	1.90	4.25	90	989.00	10.9889	64.4	9.98	9.50	4J
D.162.180.1275	16.2	1.80	12.75	270	791.00	2.9296	64.8	24.75	9.90	4J
D.166.140.0600	16.6	1.40	6.00	0	370.00	2.0556	66.4	9.80	10.70	4J
D.166.140.0875	16.6	1.40	8.75	270	370.00	1.3704	66.4	13.65	11.10	4J
D.166.140.1150	16.6	1.40	11.50	180	370.00	1.0278	66.4	17.50	11.50	4J
D.167.160.0850	16.7	1.60	8.50	180	492.00	2.5350	66.8	15.20	10.80	4J
D.168.125.0200	16.8	1.25	2.00	0	242.94	3.9696	67.2	3.75	12.80	4I
D.168.125.0225	16.8	1.25	2.25	90	242.94	3.5311	67.2	4.06	12.80	4I
D.168.125.0250	16.8	1.25	2.50	180	242.94	3.1757	67.2	4.38	12.80	4I
D.168.125.0275	16.8	1.25	2.75	270	242.94	2.8887	67.2	4.69	12.80	4I
D.168.125.0300	16.8	1.25	3.00	0	242.94	2.6493	67.2	5.00	12.80	4I
D.168.125.0325	16.8	1.25	3.25	90	242.94	2.4441	67.2	5.31	12.80	4I
D.168.125.0350	16.8	1.25	3.50	180	242.94	2.2705	67.2	5.63	12.80	4I
D.168.125.0375	16.8	1.25	3.75	270	242.94	2.1180	67.2	5.94	12.80	4I
D.168.125.0400	16.8	1.25	4.00	0	242.94	1.9864	67.2	6.25	12.80	4I
D.168.125.0525	16.8	1.25	5.25	90	242.94	1.5127	67.2	7.81	12.80	4I
D.168.125.0650	16.8	1.25	6.50	180	242.94	1.2220	67.2	9.38	12.80	4I
D.168.125.0775	16.8	1.25	7.75	270	242.94	1.0251	67.2	10.94	12.80	4I
D.172.190.0800	17.2	1.90	8.00	0	989.00	5.4944	68.8	17.10	10.70	4J
D.172.200.0425	17.2	2.00	4.25	90	1102.00	12.2444	68.8	10.50	10.30	4K
D.173.150.0600	17.3	1.50	6.00	0	475.00	2.6389	69.2	10.50	11.10	4J
D.176.160.0200	17.6	1.60	2.00	0	489.79	10.3331	70.4	4.80	13.00	4J
D.176.160.0225	17.6	1.60	2.25	90	489.79	9.1721	70.4	5.20	13.00	4J
D.176.160.0250	17.6	1.60	2.50	180	489.79	8.2595	70.4	5.60	13.00	4J
D.176.160.0275	17.6	1.60	2.75	270	489.79	7.5121	70.4	6.00	13.00	4J
D.176.160.0300	17.6	1.60	3.00	0	489.79	6.8887	70.4	6.40	13.00	4J
D.176.160.0325	17.6	1.60	3.25	90	489.79	6.3527	70.4	6.80	13.00	4J
D.176.160.0350	17.6	1.60	3.50	180	489.79	5.9011	70.4	7.20	13.00	4J
D.176.160.0375	17.6	1.60	3.75	270	489.79	5.5094	70.4	7.60	13.00	4J
D.176.160.0400	17.6	1.60	4.00	0	489.79	5.1611	70.4	8.00	13.00	4J
D.176.160.0525	17.6	1.60	5.25	90	489.79	3.9341	70.4	10.00	13.00	4J
D.176.160.0650	17.6	1.60	6.50	180	489.79	3.1784	70.4	12.00	13.00	4J
D.176.160.0775	17.6	1.60	7.75	270	489.79	2.6648	70.4	14.00	13.00	4J
D.178.150.0875	17.8	1.50	8.75	270	475.00	1.7593	71.2	14.63	11.50	4J
D.178.190.1175	17.8	1.90	11.75	270	989.00	3.6630	71.2	24.23	12.70	4J
D.180.125.0350	18.0	1.25	3.50	180	221.85	1.7177	72.0	5.63	12.00	4I
D.180.125.0525	18.0	1.25	5.25	90	221.85	1.2004	72.0	7.81	12.00	4I
D.180.125.0775	18.0	1.25	7.75	270	221.85	0.8393	72.0	10.94	12.00	4I

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.180.125.1200	18.0	1.25	12.00	0	221.85	0.5553	72.0	16.25	12.00	4I
D.180.150.1150	18.0	1.50	11.50	180	409.00	1.3180	72.0	18.75	11.87	4J
D.180.150.1250	18.0	1.50	12.50	180	475.00	1.3194	72.0	20.25	11.70	4J
D.180.200.0350	18.0	2.00	3.50	180	824.84	11.7066	72.0	9.00	10.50	4K
D.180.200.0525	18.0	2.00	5.25	90	824.84	8.1976	72.0	12.50	10.50	4K
D.180.200.0775	18.0	2.00	7.75	270	824.84	5.7397	72.0	17.50	10.50	4K
D.180.200.1200	18.0	2.00	12.00	0	824.84	3.8019	72.0	26.00	10.50	4K
D.180.300.0200	18.0	3.00	2.00	0	2820.37	136.2498	72.0	9.00	10.80	4L
D.180.300.0325	18.0	3.00	3.25	90	2820.37	83.6905	72.0	12.75	10.80	4L
D.180.300.0450	18.0	3.00	4.50	180	2820.37	60.3934	72.0	16.50	10.80	4L
D.180.300.0575	18.0	3.00	5.75	270	2820.37	47.3216	72.0	20.25	10.80	4L
D.180.300.0700	18.0	3.00	7.00	0	2820.37	38.8481	72.0	24.00	10.80	4L
D.180.300.0825	18.0	3.00	8.25	90	2820.37	32.9482	72.0	27.75	10.80	4L
D.180.300.0950	18.0	3.00	9.50	180	2820.37	28.6332	72.0	31.50	10.80	4L
D.180.300.1075	18.0	3.00	10.75	270	2820.37	25.2948	72.0	35.25	10.80	4L
D.182.220.0425	18.2	2.20	4.25	90	1356.00	15.0667	72.8	11.55	10.70	4K
D.185.200.0800	18.5	2.00	8.00	0	1102.00	6.1222	74.0	18.00	11.50	4K
D.185.200.1175	18.5	2.00	11.75	270	1102.00	4.0815	74.0	25.50	11.50	4K
D.185.200.1200	18.5	2.00	12.00	0	824.84	3.6796	74.0	26.00	12.77	4K
D.185.250.0200	18.5	2.50	2.00	0	1696.59	61.4707	74.0	7.50	12.10	4L
D.185.250.0325	18.5	2.50	3.25	90	1696.59	37.8703	74.0	10.63	12.10	4L
D.185.250.0450	18.5	2.50	4.50	180	1696.59	27.3203	74.0	13.75	12.10	4L
D.185.250.0575	18.5	2.50	5.75	270	1696.59	21.3946	74.0	16.88	12.10	4L
D.185.250.0700	18.5	2.50	7.00	0	1696.59	17.5812	74.0	20.00	12.10	4L
D.185.250.0825	18.5	2.50	8.25	90	1696.59	14.9479	74.0	23.13	12.10	4L
D.185.250.0950	18.5	2.50	9.50	180	1696.59	14.0214	74.0	26.25	12.10	4L
D.185.250.1075	18.5	2.50	10.75	270	1696.59	11.4403	74.0	29.38	12.10	4L
D.190.200.0200	19.0	2.00	2.00	0	912.63	23.7047	76.0	6.00	13.50	4K
D.190.200.0225	19.0	2.00	2.25	90	912.63	21.0769	76.0	6.50	13.50	4K
D.190.200.0250	19.0	2.00	2.50	180	912.63	18.9736	76.0	7.00	13.50	4K
D.190.200.0275	19.0	2.00	2.75	270	912.63	17.2520	76.0	7.50	13.50	4K
D.190.200.0300	19.0	2.00	3.00	0	912.63	15.8168	76.0	8.00	13.50	4K
D.190.200.0325	19.0	2.00	3.25	90	912.63	14.6021	76.0	8.50	13.50	4K
D.190.200.0350	19.0	2.00	3.50	180	912.63	13.5606	76.0	9.00	13.50	4K
D.190.200.0375	19.0	2.00	3.75	270	912.63	12.6578	76.0	9.50	13.50	4K
D.190.200.0400	19.0	2.00	4.00	0	912.63	11.8678	76.0	10.00	13.50	4K
D.190.200.0650	19.0	2.00	6.50	180	912.63	7.3010	76.0	15.00	13.50	4K
D.190.200.0775	19.0	2.00	7.75	270	912.63	6.1209	76.0	17.50	13.50	4K
D.193.220.0900	19.3	2.20	9.00	0	1356.00	7.5333	77.2	22.00	11.90	4K
D.195.160.0500	19.5	1.60	5.00	0	499.00	3.6430	78.0	9.60	12.86	4J
D.195.160.0600	19.5	1.60	6.00	0	582.00	3.2333	78.0	11.20	12.70	4J
D.196.360.0200	19.6	3.60	2.00	0	4777.41	263.9453	78.4	10.80	11.10	4L
D.196.360.0325	19.6	3.60	3.25	90	4777.41	162.4969	78.4	15.30	11.10	4L
D.196.360.0450	19.6	3.60	4.50	180	4777.41	117.3811	78.4	19.80	11.10	4L
D.196.360.0575	19.6	3.60	5.75	270	4777.41	91.8733	78.4	24.30	11.10	4L
D.196.360.0700	19.6	3.60	7.00	0	4777.41	75.4725	78.4	28.80	11.10	4L
D.196.360.0825	19.6	3.60	8.25	90	4777.41	64.0403	78.4	33.30	11.10	4L
D.196.360.0950	19.6	3.60	9.50	180	4777.41	55.6159	78.4	37.80	11.10	4L
D.196.360.1075	19.6	3.60	10.75	270	4777.41	49.1503	78.4	42.30	11.10	4L
D.197.190.0700	19.7	1.90	7.00	0	989.00	5.4944	78.8	15.20	12.30	4J

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.197.240.0525	19.7	2.40	5.25	90	1808.00	20.0889	78.8	15.00	11.50	4K
D.199.160.0875	19.9	1.60	8.75	270	582.00	2.1556	79.6	15.60	13.10	4J
D.200.140.0350	20.0	1.40	3.50	180	311.51	2.4338	80.0	6.30	13.30	4J
D.200.140.0525	20.0	1.40	5.25	90	311.51	1.7009	80.0	8.75	13.30	4J
D.200.140.0775	20.0	1.40	7.75	270	311.51	1.1893	80.0	12.25	13.30	4J
D.200.140.1200	20.0	1.40	12.00	0	311.51	0.7869	80.0	18.20	13.30	4J
D.200.220.0350	20.0	2.20	3.50	180	1033.42	15.4093	80.0	9.90	11.70	4K
D.200.220.0525	20.0	2.20	5.25	90	1033.42	10.7898	80.0	13.75	11.70	4K
D.200.220.0775	20.0	2.20	7.75	270	1033.42	7.5545	80.0	19.25	11.70	4K
D.200.220.1200	20.0	2.20	12.00	0	1033.42	5.0038	80.0	28.60	11.70	4K
D.201.220.1275	20.1	2.20	12.75	270	1356.00	5.0222	80.4	30.25	12.70	4K
D.203.160.1150	20.3	1.60	11.50	180	582.00	1.6167	81.2	20.00	13.10	4J
D.204.200.0700	20.4	2.00	7.00	0	1102.00	6.1222	81.6	16.00	12.70	4K
D.206.180.0600	20.6	1.80	6.00	0	791.00	4.3944	82.4	12.60	13.10	4J
D.210.180.0875	21.0	1.80	8.75	270	791.00	2.9296	84.0	17.55	13.50	4J
D.210.190.0975	21.0	1.90	9.75	270	989.00	3.6630	84.0	20.43	13.50	4J
D.214.180.1250	21.4	1.80	12.50	180	791.00	2.1972	85.6	24.30	13.90	4J
D.215.270.0525	21.5	2.70	5.25	90	2373.00	26.3667	86.0	16.88	12.70	4L
D.216.160.0200	21.6	1.60	2.00	0	489.79	8.2595	86.4	4.80	16.50	4J
D.216.160.0225	21.6	1.60	2.25	90	489.79	7.3432	86.4	5.20	16.50	4J
D.216.160.0250	21.6	1.60	2.50	180	489.79	6.6099	86.4	5.60	16.50	4J
D.216.160.0275	21.6	1.60	2.75	270	489.79	6.0097	86.4	6.00	16.50	4J
D.216.160.0300	21.6	1.60	3.00	0	489.79	5.5094	86.4	6.40	16.50	4J
D.216.160.0325	21.6	1.60	3.25	90	489.79	5.0861	86.4	6.80	16.50	4J
D.216.160.0350	21.6	1.60	3.50	180	489.79	4.7231	86.4	7.20	16.50	4J
D.216.160.0375	21.6	1.60	3.75	270	489.79	4.4086	86.4	7.60	16.50	4J
D.216.160.0400	21.6	1.60	4.00	0	489.79	4.1332	86.4	8.00	16.50	4J
D.216.160.0525	21.6	1.60	5.25	90	489.79	3.1478	86.4	10.00	16.50	4J
D.216.160.0650	21.6	1.60	6.50	180	489.79	2.5430	86.4	12.00	16.50	4J
D.216.160.0775	21.6	1.60	7.75	270	489.79	2.1323	86.4	14.00	16.50	4J
D.217.200.0975	21.7	2.00	9.75	270	1102.00	4.0815	86.8	21.50	13.90	4K
D.220.160.0350	22.0	1.60	3.50	180	440.02	3.7841	88.0	7.20	14.60	4J
D.220.160.0525	22.0	1.60	5.25	90	440.02	2.6449	88.0	10.00	14.60	4J
D.220.160.0775	22.0	1.60	7.75	270	440.02	1.8495	88.0	14.00	14.60	4J
D.220.160.1200	22.0	1.60	12.00	0	440.02	1.2238	88.0	20.80	14.60	4J
D.220.200.0200	22.0	2.00	2.00	0	912.63	20.1909	88.0	6.00	16.20	4K
D.220.200.0225	22.0	2.00	2.25	90	912.63	17.9299	88.0	6.50	16.20	4K
D.220.200.0250	22.0	2.00	2.50	180	912.63	16.1242	88.0	7.00	16.20	4K
D.220.200.0275	22.0	2.00	2.75	270	912.63	14.6725	88.0	7.50	16.20	4K
D.220.200.0300	22.0	2.00	3.00	0	912.63	13.4408	88.0	8.00	16.20	4K
D.220.200.0325	22.0	2.00	3.25	90	912.63	12.4167	88.0	8.50	16.20	4K
D.220.200.0350	22.0	2.00	3.50	180	912.63	11.5231	88.0	9.00	16.20	4K
D.220.200.0375	22.0	2.00	3.75	270	912.63	10.7621	88.0	9.50	16.20	4K
D.220.200.0400	22.0	2.00	4.00	0	912.63	10.0843	88.0	10.00	16.20	4K
D.220.200.0525	22.0	2.00	5.25	90	912.63	7.6821	88.0	12.50	16.20	4K
D.220.200.0650	22.0	2.00	6.50	180	912.63	6.2041	88.0	15.00	16.20	4K
D.220.200.0775	22.0	2.00	7.75	270	912.63	5.2061	88.0	17.50	16.20	4K
D.220.250.0350	22.0	2.50	3.50	180	1510.19	23.4409	88.0	11.25	12.70	4L
D.220.250.0525	22.0	2.50	5.25	90	1510.19	16.4166	88.0	15.63	12.70	4L
D.220.250.0775	22.0	2.50	7.75	270	1510.19	11.4955	88.0	21.88	12.70	4L

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.220.250.1200	22.0	2.50	12.00	0	1510.19	7.6150	88.0	32.50	12.70	4L
D.220.300.0200	22.0	3.00	2.00	0	2820.37	107.2384	88.0	9.00	14.40	4L
D.220.300.0325	22.0	3.00	3.25	90	2820.37	66.0508	88.0	12.75	14.40	4L
D.220.300.0450	22.0	3.00	4.50	180	2820.37	47.7220	88.0	16.50	14.40	4L
D.220.300.0575	22.0	3.00	5.75	270	2820.37	37.3559	88.0	20.25	14.40	4L
D.220.300.0700	22.0	3.00	7.00	0	2820.37	30.6896	88.0	24.00	14.40	4L
D.220.300.0825	22.0	3.00	8.25	90	2820.37	26.0422	88.0	27.75	14.40	4L
D.220.300.0950	22.0	3.00	9.50	180	2820.37	22.6172	88.0	31.50	14.40	4L
D.220.300.1075	22.0	3.00	10.75	270	2820.37	19.9884	88.0	35.25	14.40	4L
D.221.160.0875	22.1	1.60	8.75	270	504.00	2.1560	88.4	15.60	14.97	4J
D.221.240.0900	22.1	2.40	9.00	0	1808.00	10.0444	88.4	24.00	13.50	4K
D.225.250.0200	22.5	2.50	2.00	0	1696.59	49.1765	90.0	7.50	15.70	4L
D.225.250.0325	22.5	2.50	3.25	90	1696.59	30.2963	90.0	10.63	15.70	4L
D.225.250.0450	22.5	2.50	4.50	180	1696.59	21.8915	90.0	13.75	15.70	4L
D.225.250.0575	22.5	2.50	5.75	270	1696.59	17.1200	90.0	16.88	15.70	4L
D.225.250.0700	22.5	2.50	7.00	0	1696.59	14.0679	90.0	20.00	15.70	4L
D.225.250.0825	22.5	2.50	8.25	90	1696.59	11.9310	90.0	23.13	15.70	4L
D.225.250.0950	22.5	2.50	9.50	180	1696.59	10.3640	90.0	26.25	15.70	4L
D.225.250.1075	22.5	2.50	10.75	270	1696.59	9.1609	90.0	29.38	15.70	4L
D.229.200.1250	22.9	2.00	12.50	180	1102.00	3.0611	91.6	27.00	14.70	4K
D.235.240.1275	23.5	2.40	12.75	270	1808.00	6.6963	94.0	33.00	14.70	4K
D.246.360.0200	24.6	3.60	2.00	0	4777.41	201.5785	98.4	10.80	15.60	4L
D.246.360.0325	24.6	3.60	3.25	90	4777.41	124.0886	98.4	15.30	15.60	4L
D.246.360.0450	24.6	3.60	4.50	180	4777.41	89.4646	98.4	19.80	15.60	4L
D.246.360.0575	24.6	3.60	5.75	270	4777.41	70.0500	98.4	24.30	15.60	4L
D.246.360.0700	24.6	3.60	7.00	0	4777.41	57.5592	98.4	28.80	15.60	4L
D.246.360.0825	24.6	3.60	8.25	90	4777.41	48.8488	98.4	33.30	15.60	4L
D.246.360.0950	24.6	3.60	9.50	180	4777.41	42.4282	98.4	37.80	15.60	4L
D.246.360.1075	24.6	3.60	10.75	270	4777.41	37.4699	98.4	42.30	15.60	4L
D.248.190.1050	24.8	1.90	10.50	180	989.00	2.7472	99.2	21.85	16.30	4J
D.248.290.0525	24.8	2.90	5.25	90	3164.00	35.1556	99.2	18.13	15.10	4L
D.249.270.0900	24.9	2.70	9.00	0	2373.00	13.1833	99.6	27.00	15.50	4L
D.250.180.0350	25.0	1.80	3.50	180	626.96	5.3304	100.0	8.10	16.70	4J
D.250.180.0525	25.0	1.80	5.25	90	626.96	3.7256	100.0	11.25	16.70	4J
D.250.180.0775	25.0	1.80	7.75	270	626.96	2.6051	100.0	15.75	16.70	4J
D.250.180.1200	25.0	1.80	12.00	0	626.96	1.7238	100.0	23.40	16.70	4J
D.250.280.0350	25.0	2.80	3.50	180	2125.68	32.4076	100.0	12.60	14.50	4L
D.250.280.0525	25.0	2.80	5.25	90	2125.68	22.6945	100.0	17.50	14.50	4L
D.250.280.0775	25.0	2.80	7.75	270	2125.68	15.8906	100.0	24.50	14.50	4L
D.250.280.1200	25.0	2.80	12.00	0	2125.68	10.5259	100.0	36.40	14.50	4L
D.251.320.0625	25.1	3.20	6.25	90	3616.00	40.1778	100.4	23.20	15.00	4L
D.252.220.0600	25.2	2.20	6.00	0	1356.00	7.5333	100.8	15.40	16.30	4K
D.255.400.0200	25.5	4.00	2.00	0	6165.41	285.4356	102.0	12.00	15.70	4N
D.255.400.0325	25.5	4.00	3.25	90	6165.41	176.1546	102.0	17.00	15.70	4N
D.255.400.0450	25.5	4.00	4.50	180	6165.41	127.1219	102.0	22.00	15.70	4N
D.255.400.0575	25.5	4.00	5.75	270	6165.41	99.4421	102.0	27.00	15.70	4N
D.255.400.0700	25.5	4.00	7.00	0	6165.41	81.6611	102.0	32.00	15.70	4N
D.255.400.0825	25.5	4.00	8.25	90	6165.41	69.3522	102.0	37.00	15.70	4N
D.255.400.0950	25.5	4.00	9.50	180	6165.41	60.2091	102.0	42.00	15.70	4N
D.255.400.1075	25.5	4.00	10.75	270	6165.41	53.1959	102.0	47.00	15.70	4N

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.264.220.0875	26.4	2.20	8.75	270	1356.00	5.0222	105.6	21.45	17.10	4K
D.265.290.0900	26.5	2.90	9.00	0	3164.00	17.5778	106.0	29.00	16.30	4L
D.268.220.1250	26.8	2.20	12.50	180	1356.00	3.7667	107.2	29.70	17.50	4K
D.270.200.0200	27.0	2.00	2.00	0	912.63	16.1527	108.0	6.00	20.70	4K
D.270.200.0225	27.0	2.00	2.25	90	912.63	14.3495	108.0	6.50	20.70	4K
D.270.200.0250	27.0	2.00	2.50	180	912.63	12.9085	108.0	7.00	20.70	4K
D.270.200.0275	27.0	2.00	2.75	270	912.63	11.7305	108.0	7.50	20.70	4K
D.270.200.0300	27.0	2.00	3.00	0	912.63	10.7621	108.0	8.00	20.70	4K
D.270.200.0325	27.0	2.00	3.25	90	912.63	9.9307	108.0	8.50	20.70	4K
D.270.200.0350	27.0	2.00	3.50	180	912.63	9.2185	108.0	9.00	20.70	4K
D.270.200.0375	27.0	2.00	3.75	270	912.63	8.6097	108.0	9.50	20.70	4K
D.270.200.0400	27.0	2.00	4.00	0	912.63	8.0692	108.0	10.00	20.70	4K
D.270.200.0525	27.0	2.00	5.25	90	912.63	6.1498	108.0	12.50	20.70	4K
D.270.200.0650	27.0	2.00	6.50	180	912.63	4.9653	108.0	15.00	20.70	4K
D.270.200.0775	27.0	2.00	7.75	270	912.63	4.1654	108.0	17.50	20.70	4K
D.270.300.0200	27.0	3.00	2.00	0	2820.37	84.9509	108.0	9.00	18.90	4L
D.270.300.0325	27.0	3.00	3.25	90	2820.37	52.3260	108.0	12.75	18.90	4L
D.270.300.0450	27.0	3.00	4.50	180	2820.37	37.8066	108.0	16.50	18.90	4L
D.270.300.0575	27.0	3.00	5.75	270	2820.37	29.5946	108.0	20.25	18.90	4L
D.270.300.0700	27.0	3.00	7.00	0	2820.37	24.3135	108.0	24.00	18.90	4L
D.270.300.0825	27.0	3.00	8.25	90	2820.37	20.6167	108.0	27.75	18.90	4L
D.270.300.0950	27.0	3.00	9.50	180	2820.37	17.9071	108.0	31.50	18.90	4L
D.270.300.1075	27.0	3.00	10.75	270	2820.37	15.8270	108.0	35.25	18.90	4L
D.275.250.0200	27.5	2.50	2.00	0	1696.59	39.3640	110.0	7.50	20.20	4L
D.275.250.0325	27.5	2.50	3.25	90	1696.59	24.2370	110.0	10.63	20.20	4L
D.275.250.0450	27.5	2.50	4.50	180	1696.59	17.5087	110.0	13.75	20.20	4L
D.275.250.0575	27.5	2.50	5.75	270	1696.59	13.7043	110.0	16.88	20.20	4L
D.275.250.0700	27.5	2.50	7.00	0	1696.59	11.2581	110.0	20.00	20.20	4L
D.275.250.0825	27.5	2.50	8.25	90	1696.59	9.5529	110.0	23.13	20.20	4L
D.275.250.0950	27.5	2.50	9.50	180	1696.59	8.2922	110.0	26.25	20.20	4L
D.275.250.1075	27.5	2.50	10.75	270	1696.59	7.3287	110.0	29.38	20.20	4L
D.275.320.1100	27.5	3.20	11.00	0	3616.00	20.0889	110.0	38.40	16.90	4L
D.276.290.1275	27.6	2.90	12.75	270	3164.00	11.7185	110.4	39.88	17.50	4L
D.277.270.1175	27.7	2.70	11.75	270	2373.00	8.7889	110.8	34.43	17.90	4L
D.280.200.0350	28.0	2.00	3.50	180	860.53	7.2501	112.0	9.00	18.70	4K
D.280.200.0525	28.0	2.00	5.25	90	860.53	5.0672	112.0	12.50	18.70	4K
D.280.200.0775	28.0	2.00	7.75	270	860.53	3.5432	112.0	17.50	18.70	4K
D.280.200.1200	28.0	2.00	12.00	0	860.53	2.3445	112.0	26.00	18.70	4K
D.280.320.0350	28.0	3.20	3.50	180	2963.17	49.4709	112.0	14.40	16.20	4L
D.280.320.0525	28.0	3.20	5.25	90	2963.17	34.6475	112.0	20.00	16.20	4L
D.280.320.0775	28.0	3.20	7.75	270	2963.17	24.2621	112.0	28.00	16.20	4L
D.280.320.1200	28.0	3.20	12.00	0	2963.17	16.0722	112.0	41.60	16.20	4L
D.280.340.0625	28.0	3.40	6.25	90	4519.00	50.2111	112.0	24.65	16.90	4L
D.287.240.0700	28.7	2.40	7.00	0	1808.00	10.0444	114.8	19.20	18.60	4K
D.296.360.0200	29.6	3.60	2.00	0	4777.41	163.0515	118.4	10.80	20.10	4L
D.296.360.0325	29.6	3.60	3.25	90	4777.41	100.1553	118.4	15.30	20.10	4L
D.296.360.0450	29.6	3.60	4.50	180	4777.41	72.3850	118.4	19.80	20.10	4L
D.296.360.0575	29.6	3.60	5.75	270	4777.41	56.6044	118.4	24.30	20.10	4L
D.296.360.0700	29.6	3.60	7.00	0	4777.41	46.5181	118.4	28.80	20.10	4L
D.296.360.0825	29.6	3.60	8.25	90	4777.41	39.4827	118.4	33.30	20.10	4L

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.296.360.0950	29.6	3.60	9.50	180	4777.41	34.2712	118.4	37.80	20.10	4L
D.296.360.1075	29.6	3.60	10.75	270	4777.41	30.2943	118.4	42.30	20.10	4L
D.302.320.1475	30.2	3.20	14.75	270	3616.00	13.3926	120.8	50.40	19.10	4L
D.302.340.1100	30.2	3.40	11.00	0	4519.00	25.1056	120.8	40.80	18.70	4L
D.305.400.0200	30.5	4.00	2.00	0	6165.41	231.7823	122.0	12.00	20.20	4N
D.305.400.0325	30.5	4.00	3.25	90	6165.41	142.7178	122.0	17.00	20.20	4N
D.305.400.0450	30.5	4.00	4.50	180	6165.41	103.1005	122.0	22.00	20.20	4N
D.305.400.0575	30.5	4.00	5.75	270	6165.41	80.6991	122.0	27.00	20.20	4N
D.305.400.0700	30.5	4.00	7.00	0	6165.41	66.2947	122.0	32.00	20.20	4N
D.305.400.0825	30.5	4.00	8.25	90	6165.41	56.2537	122.0	37.00	20.20	4N
D.305.400.0950	30.5	4.00	9.50	180	6165.41	48.8543	122.0	42.00	20.20	4N
D.305.400.1075	30.5	4.00	10.75	270	6165.41	43.1751	122.0	47.00	20.20	4N
D.306.240.0875	30.6	2.40	8.75	270	1808.00	6.6963	122.4	23.40	20.20	4K
D.311.240.1250	31.1	2.40	12.50	180	1808.00	5.0222	124.4	32.40	20.60	4K
D.312.130.0350	31.2	1.30	3.50	180	315.00	1.4330	124.8	5.85	20.68	4I
D.317.270.0700	31.7	2.70	7.00	0	2373.00	13.1833	126.8	21.60	20.60	4L
D.320.300.0200	32.0	3.00	2.00	0	2820.37	70.3334	128.0	9.00	23.40	4L
D.320.300.0325	32.0	3.00	3.25	90	2820.37	43.3237	128.0	12.75	23.40	4L
D.320.300.0450	32.0	3.00	4.50	180	2820.37	31.3027	128.0	16.50	23.40	4L
D.320.300.0575	32.0	3.00	5.75	270	2820.37	24.5036	128.0	20.25	23.40	4L
D.320.300.0700	32.0	3.00	7.00	0	2820.37	20.1168	128.0	24.00	23.40	4L
D.320.300.0825	32.0	3.00	8.25	90	2820.37	17.0725	128.0	27.75	23.40	4L
D.320.300.0950	32.0	3.00	9.50	180	2820.37	14.8284	128.0	31.50	23.40	4L
D.320.300.1075	32.0	3.00	10.75	270	2820.37	13.0997	128.0	35.25	23.40	4L
D.330.340.1475	33.0	3.40	14.75	270	4519.00	16.7370	132.0	53.55	21.00	4L
D.341.270.0975	34.1	2.70	9.75	270	2373.00	8.7889	136.4	29.03	22.60	4L
D.342.290.0700	34.2	2.90	7.00	0	3164.00	17.5778	136.8	23.20	21.80	4L
D.344.320.0800	34.4	3.20	8.00	0	3616.00	20.0889	137.6	28.80	22.50	4L
D.346.360.0200	34.6	3.60	2.00	0	4777.41	136.4974	138.4	10.80	24.60	4L
D.346.360.0325	34.6	3.60	3.25	90	4777.41	84.1093	138.4	15.30	24.60	4L
D.346.360.0450	34.6	3.60	4.50	180	4777.41	60.7041	138.4	19.80	24.60	4L
D.346.360.0575	34.6	3.60	5.75	270	4777.41	47.4892	138.4	24.30	24.60	4L
D.346.360.0700	34.6	3.60	7.00	0	4777.41	39.0311	138.4	28.80	24.60	4L
D.346.360.0825	34.6	3.60	8.25	90	4777.41	33.1075	138.4	33.30	24.60	4L
D.346.360.0950	34.6	3.60	9.50	180	4777.41	28.7623	138.4	37.80	24.60	4L
D.346.360.1075	34.6	3.60	10.75	270	4777.41	25.4118	138.4	42.30	24.60	4L
D.348.270.1250	34.8	2.70	12.50	180	2373.00	6.5917	139.2	36.45	23.00	4L
D.355.400.0200	35.5	4.00	2.00	0	6165.41	195.1079	142.0	12.00	24.70	4N
D.355.400.0325	35.5	4.00	3.25	90	6165.41	120.1834	142.0	17.00	24.70	4N
D.355.400.0450	35.5	4.00	4.50	180	6165.41	86.8368	142.0	22.00	24.70	4N
D.355.400.0575	35.5	4.00	5.75	270	6165.41	67.9759	142.0	27.00	24.70	4N
D.355.400.0700	35.5	4.00	7.00	0	6165.41	55.7956	142.0	32.00	24.70	4N
D.355.400.0825	35.5	4.00	8.25	90	6165.41	47.3534	142.0	37.00	24.70	4N
D.355.400.0950	35.5	4.00	9.50	180	6165.41	41.1302	142.0	42.00	24.70	4N
D.355.400.1075	35.5	4.00	10.75	270	6165.41	36.3312	142.0	47.00	24.70	4N
D.364.290.0975	36.4	2.90	9.75	270	3164.00	11.7185	145.6	31.18	23.80	4L
D.372.290.1250	37.2	2.90	12.50	180	3164.00	8.7889	148.8	39.15	24.60	4L
D.379.340.0800	37.9	3.40	8.00	0	4519.00	25.1056	151.6	30.60	24.80	4L
D.385.320.1075	38.5	3.20	10.75	270	3616.00	13.3926	154.0	37.60	25.70	4L
D.405.400.0200	40.5	4.00	2.00	0	6165.41	168.4538	162.0	12.00	29.20	4N

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
D.405.400.0325	40.5	4.00	3.25	90	6165.41	103.7948	162.0	17.00	29.20	4N
D.405.400.0450	40.5	4.00	4.50	180	6165.41	74.9139	162.0	22.00	29.20	4N
D.405.400.0575	40.5	4.00	5.75	270	6165.41	58.6623	162.0	27.00	29.20	4N
D.405.400.0700	40.5	4.00	7.00	0	6165.41	48.1673	162.0	32.00	29.20	4N
D.405.400.0825	40.5	4.00	8.25	90	6165.41	40.8847	162.0	37.00	29.20	4N
D.405.400.0950	40.5	4.00	9.50	180	6165.41	35.4946	162.0	42.00	29.20	4N
D.405.400.1075	40.5	4.00	10.75	270	6165.41	31.3761	162.0	47.00	29.20	4N
D.408.320.1450	40.8	3.20	14.50	180	3616.00	10.0444	163.2	49.60	27.50	4L
D.422.340.1075	42.2	3.40	10.75	270	4519.00	16.7370	168.8	39.95	28.20	4L
D.446.340.1350	44.6	3.40	13.50	180	4519.00	12.5528	178.4	49.30	30.20	4L
G.024.030.0325	2.4	0.30	3.25	90	5.31	0.0590	9.6	1.28	1.40	4E
G.026.030.0975	2.6	0.30	9.75	270	5.31	0.0197	10.4	3.23	1.60	4E
G.028.020.0350	2.8	0.20	3.50	180	1.17	0.0073	11.2	0.90	1.80	4E
G.028.020.0525	2.8	0.20	5.25	90	1.11	0.0051	11.2	1.25	1.80	4E
G.028.020.0775	2.8	0.20	7.75	270	1.11	0.0035	11.2	1.75	1.80	4E
G.028.020.1200	2.8	0.20	12.00	0	1.11	0.0023	11.2	2.60	1.80	4E
G.028.030.0600	2.8	0.30	6.00	0	5.31	0.0295	11.2	2.10	1.70	4E
G.028.032.0350	2.8	0.32	3.50	180	4.15	0.0495	11.2	1.44	1.50	4E
G.028.032.0525	2.8	0.32	5.25	90	4.15	0.0346	11.2	2.00	1.50	4E
G.028.032.0775	2.8	0.32	7.75	270	4.15	0.0243	11.2	2.80	1.50	4E
G.028.032.1200	2.8	0.32	12.00	0	4.15	0.0161	11.2	4.16	1.50	4E
G.028.040.0425	2.8	0.40	4.25	90	10.51	0.1168	11.2	2.10	1.60	4E
G.032.022.0350	3.2	0.22	3.50	180	1.49	0.0093	12.8	0.99	2.10	4E
G.032.022.0525	3.2	0.22	5.25	90	1.49	0.0065	12.8	1.38	2.10	4E
G.032.022.0575	3.2	0.22	5.75	270	1.49	0.0045	12.8	1.49	2.10	4E
G.032.022.0775	3.2	0.22	7.75	270	1.49	0.0045	12.8	1.93	2.29	4E
G.032.022.1200	3.2	0.22	12.00	0	1.49	0.0030	12.8	2.86	2.10	4E
G.032.035.0350	3.2	0.35	3.50	180	5.46	0.0617	12.8	1.58	1.80	4E
G.032.035.0525	3.2	0.35	5.25	90	5.46	0.0432	12.8	2.19	1.80	4E
G.032.035.0775	3.2	0.35	7.75	270	5.46	0.0302	12.8	3.06	1.80	4E
G.032.035.1200	3.2	0.35	12.00	0	5.46	0.0200	12.8	4.55	1.80	4E
G.032.036.0325	3.2	0.36	3.25	90	7.91	0.0879	12.8	1.53	1.60	4E
G.032.036.1075	3.2	0.36	10.75	270	7.91	0.0293	12.8	4.23	1.60	4E
G.032.040.0975	3.2	0.40	9.75	270	10.51	0.0389	12.8	4.30	2.00	4E
G.033.040.0600	3.3	0.40	6.00	0	10.51	0.0584	13.2	2.80	2.00	4E
G.034.036.0700	3.4	0.36	7.00	0	7.91	0.0439	13.6	2.88	2.00	4E
G.035.050.0200	3.5	0.50	2.00	0	17.18	0.5254	14.0	1.50	2.25	4E
G.035.050.0325	3.5	0.50	3.25	90	17.18	0.3229	14.0	2.13	2.25	4E
G.035.050.0450	3.5	0.50	4.50	180	17.18	0.2331	14.0	2.75	2.25	4E
G.035.050.0575	3.5	0.50	5.75	270	17.18	0.1826	14.0	3.38	2.25	4E
G.035.050.0700	3.5	0.50	7.00	0	17.18	0.1499	14.0	4.00	2.25	4E
G.035.050.0825	3.5	0.50	8.25	90	17.18	0.1273	14.0	4.63	2.25	4E
G.035.050.0950	3.5	0.50	9.50	180	17.18	0.1105	14.0	5.25	2.25	4E
G.035.050.1075	3.5	0.50	10.75	270	17.18	0.0976	14.0	5.88	2.25	4E
G.036.025.0350	3.6	0.25	3.50	180	2.08	0.0137	14.4	1.13	2.30	4E
G.036.025.0525	3.6	0.25	5.25	90	2.08	0.0096	14.4	1.56	2.30	4E
G.036.025.0775	3.6	0.25	7.75	270	2.08	0.0067	14.4	2.19	2.30	4E
G.036.025.1200	3.6	0.25	12.00	0	2.08	0.0044	14.4	3.25	2.30	4E
G.036.040.0350	3.6	0.40	3.50	180	8.14	0.0937	14.4	1.80	2.00	4E
G.036.040.0525	3.6	0.40	5.25	90	8.14	0.0656	14.4	2.50	2.00	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.036.040.0775	3.6	0.40	7.75	270	8.14	0.0459	14.4	3.50	2.00	4E
G.036.040.1200	3.6	0.40	12.00	0	8.14	0.0304	14.4	5.20	2.00	4E
G.040.028.0350	4.0	0.28	3.50	180	2.92	0.0195	16.0	1.26	2.60	4E
G.040.028.0525	4.0	0.28	5.25	90	2.92	0.0136	16.0	1.75	2.60	4E
G.040.028.0775	4.0	0.28	7.75	270	2.92	0.0095	16.0	2.45	2.60	4E
G.040.028.1200	4.0	0.28	12.00	0	2.92	0.0063	16.0	3.64	2.60	4E
G.040.045.0350	4.0	0.45	3.50	180	11.01	0.1352	16.0	2.03	2.30	4E
G.040.045.0525	4.0	0.45	5.25	90	11.01	0.0947	16.0	2.81	2.30	4E
G.040.045.0775	4.0	0.45	7.75	270	11.01	0.0663	16.0	3.94	2.30	4E
G.040.045.1200	4.0	0.45	12.00	0	11.01	0.0439	16.0	5.85	2.30	4E
G.041.045.0325	4.1	0.45	3.25	90	13.22	0.1469	16.4	1.91	2.40	4E
G.041.045.0975	4.1	0.45	9.75	270	13.22	0.0490	16.4	4.84	2.40	4E
G.041.045.1075	4.1	0.45	10.75	270	15.82	0.0586	16.4	5.29	2.80	4E
G.042.030.0400	4.2	0.30	4.00	0	5.31	0.0295	16.8	1.50	2.80	4E
G.042.045.0700	4.2	0.45	7.00	0	15.82	0.0879	16.8	3.60	2.80	4E
G.043.030.0475	4.3	0.30	4.75	270	5.31	0.0197	17.2	1.73	2.80	4E
G.044.030.0650	4.4	0.30	6.50	180	5.31	0.0148	17.6	2.25	2.80	4E
G.044.045.0600	4.4	0.45	6.00	0	13.22	0.0734	17.6	3.15	2.40	4E
G.044.050.1175	4.4	0.50	11.75	270	21.10	0.0781	17.6	6.38	2.40	4E
G.045.032.0350	4.5	0.32	3.50	180	4.35	0.0296	18.0	1.44	2.90	4E
G.045.032.0525	4.5	0.32	5.25	90	4.35	0.0207	18.0	2.00	2.90	4E
G.045.032.0775	4.5	0.32	7.75	270	4.35	0.0144	18.0	2.80	2.90	4E
G.045.032.1200	4.5	0.32	12.00	0	4.35	0.0096	18.0	4.16	2.90	4E
G.045.045.0325	4.5	0.45	3.25	90	15.82	0.1758	18.0	1.91	2.80	4E
G.045.050.0200	4.5	0.50	2.00	0	17.18	0.3940	18.0	1.50	3.15	4E
G.045.050.0325	4.5	0.50	3.25	90	17.18	0.2423	18.0	2.13	3.15	4E
G.045.050.0350	4.5	0.50	3.50	180	15.13	0.1829	18.0	2.25	2.60	4E
G.045.050.0450	4.5	0.50	4.50	180	17.18	0.1749	18.0	2.75	3.15	4E
G.045.050.0525	4.5	0.50	5.25	90	15.13	0.1281	18.0	3.13	2.60	4E
G.045.050.0575	4.5	0.50	5.75	270	17.18	0.1370	18.0	3.38	3.15	4E
G.045.050.0700	4.5	0.50	7.00	0	17.18	0.1125	18.0	4.00	3.15	4E
G.045.050.0775	4.5	0.50	7.75	270	15.13	0.0897	18.0	4.38	2.60	4E
G.045.050.0825	4.5	0.50	8.25	90	17.18	0.0955	18.0	4.63	3.15	4E
G.045.050.0950	4.5	0.50	9.50	180	17.18	0.0829	18.0	5.25	3.15	4E
G.045.050.1075	4.5	0.50	10.75	270	17.18	0.0733	18.0	5.88	3.15	4E
G.045.050.1200	4.5	0.50	12.00	0	15.13	0.0594	18.0	6.50	2.60	4E
G.046.040.0400	4.6	0.40	4.00	0	10.51	0.0584	18.4	2.00	2.80	4E
G.046.050.0700	4.6	0.50	7.00	0	21.10	0.1172	18.4	4.00	2.80	4E
G.046.063.0200	4.6	0.63	2.00	0	33.75	0.9926	18.4	1.89	3.00	4E
G.046.063.0325	4.6	0.63	3.25	90	33.75	0.6103	18.4	2.68	3.00	4E
G.046.063.0450	4.6	0.63	4.50	180	33.75	0.4412	18.4	3.47	3.00	4E
G.046.063.0575	4.6	0.63	5.75	270	33.75	0.3451	18.4	4.25	3.00	4E
G.046.063.0700	4.6	0.63	7.00	0	33.75	0.2834	18.4	5.04	3.00	4E
G.046.063.0825	4.6	0.63	8.25	90	33.75	0.2406	18.4	5.83	3.00	4E
G.046.063.0950	4.6	0.63	9.50	180	33.75	0.2088	18.4	6.62	3.00	4E
G.046.063.1075	4.6	0.63	10.75	270	33.75	0.1845	18.4	7.40	3.00	4E
G.047.055.0325	4.7	0.55	3.25	90	24.60	0.2733	18.8	2.34	2.80	4E
G.047.055.0700	4.7	0.55	7.00	0	24.60	0.1367	18.8	4.40	2.80	4E
G.047.055.0725	4.7	0.55	7.25	90	20.16	0.1343	18.8	4.54	3.15	4E
G.047.055.1075	4.7	0.55	10.75	270	24.60	0.0911	18.8	6.46	2.80	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.048.050.0325	4.8	0.50	3.25	90	21.10	0.2344	19.2	2.13	2.80	4E
G.048.056.0700	4.8	0.56	7.00	0	34.80	0.1933	19.2	4.48	2.80	4E
G.048.056.0725	4.8	0.56	7.25	90	20.16	0.1413	19.2	4.62	3.23	4E
G.048.056.1075	4.8	0.56	10.75	270	34.80	0.1289	19.2	6.58	2.80	4E
G.049.036.0400	4.9	0.36	4.00	0	7.91	0.0439	19.6	1.80	2.80	4E
G.050.035.0350	5.0	0.35	3.50	180	5.70	0.0380	20.0	1.58	3.30	4E
G.050.035.0525	5.0	0.35	5.25	90	5.70	0.0266	20.0	2.19	3.30	4E
G.050.035.0775	5.0	0.35	7.75	270	5.70	0.0186	20.0	3.06	3.30	4E
G.050.035.1200	5.0	0.35	12.00	0	5.70	0.0123	20.0	4.55	3.30	4E
G.050.040.0575	5.0	0.40	5.75	270	10.51	0.0389	20.0	2.70	2.80	4E
G.050.055.0350	5.0	0.55	3.50	180	20.16	0.2408	20.0	2.48	2.90	4E
G.050.055.0525	5.0	0.55	5.25	90	20.16	0.1686	20.0	3.44	2.90	4E
G.050.055.0775	5.0	0.55	7.75	270	20.16	0.1180	20.0	4.81	2.90	4E
G.050.055.1200	5.0	0.55	12.00	0	20.16	0.0782	20.0	7.15	2.90	4E
G.051.036.0575	5.1	0.36	5.75	270	7.91	0.0293	20.4	2.43	3.20	4E
G.052.036.0850	5.2	0.36	8.50	180	7.91	0.0220	20.8	3.42	3.20	4E
G.052.056.0325	5.2	0.56	3.25	90	34.80	0.3867	20.8	2.38	2.80	4E
G.053.040.0750	5.3	0.40	7.50	180	10.51	0.0292	21.2	3.40	2.80	4E
G.055.045.0500	5.5	0.45	5.00	0	15.82	0.0879	22.0	2.70	3.60	4E
G.055.050.0200	5.5	0.50	2.00	0	17.18	0.3152	22.0	1.50	4.00	4E
G.055.050.0325	5.5	0.50	3.25	90	17.18	0.1939	22.0	2.13	4.00	4E
G.055.050.0450	5.5	0.50	4.50	180	17.18	0.1400	22.0	2.75	4.00	4E
G.055.050.0575	5.5	0.50	5.75	270	17.18	0.1096	22.0	3.38	4.00	4E
G.055.050.0700	5.5	0.50	7.00	0	17.18	0.0900	22.0	4.00	4.00	4E
G.055.050.0825	5.5	0.50	8.25	90	17.18	0.0764	22.0	4.63	4.00	4E
G.055.050.0950	5.5	0.50	9.50	180	17.18	0.0664	22.0	5.25	4.00	4E
G.055.050.1075	5.5	0.50	10.75	270	17.18	0.0586	22.0	5.88	4.00	4E
G.056.040.0350	5.6	0.40	3.50	180	8.49	0.0580	22.4	1.80	3.70	4E
G.056.040.0525	5.6	0.40	5.25	90	8.49	0.0405	22.4	2.50	3.70	4E
G.056.040.0775	5.6	0.40	7.75	270	8.49	0.0283	22.4	3.50	3.70	4E
G.056.040.1200	5.6	0.40	12.00	0	8.49	0.0188	22.4	5.20	3.70	4E
G.056.060.0350	5.6	0.60	3.50	180	26.26	0.3036	22.4	2.70	3.30	4E
G.056.060.0525	5.6	0.60	5.25	90	26.26	0.2126	22.4	3.75	3.30	4E
G.056.060.0775	5.6	0.60	7.75	270	26.26	0.1488	22.4	5.25	3.30	4E
G.056.060.1200	5.6	0.60	12.00	0	26.26	0.0986	22.4	7.80	3.30	4E
G.056.063.0200	5.6	0.63	2.00	0	33.75	0.7941	22.4	1.89	3.90	4E
G.056.063.0325	5.6	0.63	3.25	90	33.75	0.4884	22.4	2.68	3.90	4E
G.056.063.0450	5.6	0.63	4.50	180	33.75	0.3530	22.4	3.47	3.90	4E
G.056.063.0575	5.6	0.63	5.75	270	33.75	0.2762	22.4	4.25	3.90	4E
G.056.063.0700	5.6	0.63	7.00	0	33.75	0.2268	22.4	5.04	3.90	4E
G.056.063.0825	5.6	0.63	8.25	90	33.75	0.1923	22.4	5.83	3.90	4E
G.056.063.0950	5.6	0.63	9.50	180	33.75	0.1663	22.4	6.62	3.90	4E
G.056.063.1075	5.6	0.63	10.75	270	33.75	0.1477	22.4	7.40	3.90	4E
G.056.065.1075	5.6	0.65	10.75	270	42.40	0.1570	22.4	7.64	3.60	4E
G.057.065.0700	5.7	0.65	7.00	0	42.40	0.2356	22.8	5.20	3.60	4E
G.057.070.0200	5.7	0.70	2.00	0	45.83	1.2092	22.8	2.10	3.80	4E
G.057.070.0325	5.7	0.70	3.25	90	45.83	0.7452	22.8	2.98	3.80	4E
G.057.070.0450	5.7	0.70	4.50	180	45.83	0.5379	22.8	3.85	3.80	4E
G.057.070.0575	5.7	0.70	5.75	270	45.83	0.4208	22.8	4.73	3.80	4E
G.057.070.0700	5.7	0.70	7.00	0	45.83	0.3456	22.8	5.60	3.80	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.057.070.0825	5.7	0.70	8.25	90	45.83	0.2934	22.8	6.48	3.80	4E
G.057.070.0950	5.7	0.70	9.50	180	45.83	0.2546	22.8	7.35	3.80	4E
G.057.070.1075	5.7	0.70	10.75	270	45.83	0.2251	22.8	8.23	3.80	4E
G.059.045.0950	5.9	0.45	9.50	180	15.82	0.0439	23.6	4.73	4.00	4E
G.060.045.0850	6.0	0.45	8.50	180	13.22	0.0367	24.0	4.28	3.60	4E
G.060.065.0325	6.0	0.65	3.25	90	42.40	0.4711	24.0	2.76	3.60	4E
G.060.080.0200	6.0	0.80	2.00	0	67.41	1.9826	24.0	2.40	4.00	4E
G.060.080.0225	6.0	0.80	2.25	90	67.41	1.7647	24.0	2.60	4.00	4E
G.060.080.0250	6.0	0.80	2.50	180	67.41	1.5861	24.0	2.80	4.00	4E
G.060.080.0275	6.0	0.80	2.75	270	67.41	1.4435	24.0	3.00	4.00	4E
G.060.080.0300	6.0	0.80	3.00	0	67.41	1.3244	24.0	3.20	4.00	4E
G.060.080.0325	6.0	0.80	3.25	90	67.41	1.2212	24.0	3.40	4.00	4E
G.060.080.0350	6.0	0.80	3.50	180	67.41	1.1348	24.0	3.60	4.00	4E
G.060.080.0375	6.0	0.80	3.75	270	67.41	1.0582	24.0	3.80	4.00	4E
G.060.080.0400	6.0	0.80	4.00	0	67.41	0.9928	24.0	4.00	4.00	4E
G.060.080.0525	6.0	0.80	5.25	90	67.41	0.7557	24.0	5.00	4.00	4E
G.060.080.0650	6.0	0.80	6.50	180	67.41	0.6106	24.0	6.00	4.00	4E
G.060.080.0775	6.0	0.80	7.75	270	67.41	0.5122	24.0	7.00	4.00	4E
G.062.045.0675	6.2	0.45	6.75	270	15.82	0.0586	24.8	3.49	4.00	4E
G.062.050.0500	6.2	0.50	5.00	0	21.10	0.1172	24.8	3.00	3.60	4E
G.062.070.1075	6.2	0.70	10.75	270	58.20	0.2156	24.8	8.23	3.60	4E
G.063.045.0350	6.3	0.45	3.50	180	11.50	0.0826	25.2	2.03	4.10	4E
G.063.045.0400	6.3	0.45	4.00	0	13.22	0.0734	25.2	2.25	4.00	4E
G.063.045.0525	6.3	0.45	5.25	90	11.50	0.0577	25.2	2.81	4.10	4E
G.063.045.0775	6.3	0.45	7.75	270	11.50	0.0404	25.2	3.94	4.10	4E
G.063.045.1200	6.3	0.45	12.00	0	11.50	0.0267	25.2	5.85	4.10	4E
G.063.055.0500	6.3	0.55	5.00	0	24.60	0.1367	25.2	3.30	4.00	4E
G.063.070.0350	6.3	0.70	3.50	180	41.51	0.5019	25.2	3.15	3.60	4E
G.063.070.0525	6.3	0.70	5.25	90	41.51	0.3515	25.2	4.38	3.60	4E
G.063.070.0700	6.3	0.70	7.00	0	58.20	0.3233	25.2	5.60	3.60	4E
G.063.070.0775	6.3	0.70	7.75	270	41.51	0.2461	25.2	6.13	3.60	4E
G.063.070.1200	6.3	0.70	12.00	0	41.51	0.1630	25.2	9.10	3.60	4E
G.064.050.1050	6.4	0.50	10.50	180	21.10	0.0586	25.6	5.75	4.00	4E
G.064.056.0775	6.4	0.56	7.75	270	34.80	0.1289	25.6	4.90	4.00	4E
G.065.050.0200	6.5	0.50	2.00	0	17.18	0.2627	26.0	1.50	5.00	4E
G.065.050.0325	6.5	0.50	3.25	90	17.18	0.1616	26.0	2.13	5.00	4E
G.065.050.0450	6.5	0.50	4.50	180	17.18	0.1167	26.0	2.75	5.00	4E
G.065.050.0575	6.5	0.50	5.75	270	17.18	0.0914	26.0	3.38	5.00	4E
G.065.050.0700	6.5	0.50	7.00	0	17.18	0.0751	26.0	4.00	5.00	4E
G.065.050.0825	6.5	0.50	8.25	90	17.18	0.0637	26.0	4.63	5.00	4E
G.065.050.0950	6.5	0.50	9.50	180	17.18	0.0553	26.0	5.25	5.00	4E
G.065.050.1075	6.5	0.50	10.75	270	17.18	0.0489	26.0	5.88	5.00	4E
G.066.045.0575	6.6	0.45	5.75	270	13.22	0.0490	26.4	3.04	4.00	4E
G.066.056.0500	6.6	0.56	5.00	0	34.80	0.1933	26.4	3.36	4.00	4E
G.066.063.0200	6.6	0.63	2.00	0	33.75	0.6618	26.4	1.89	4.80	4E
G.066.063.0325	6.6	0.63	3.25	90	33.75	0.4071	26.4	2.68	4.80	4E
G.066.063.0450	6.6	0.63	4.50	180	33.75	0.2942	26.4	3.47	4.80	4E
G.066.063.0575	6.6	0.63	5.75	270	33.75	0.2302	26.4	4.25	4.80	4E
G.066.063.0700	6.6	0.63	7.00	0	33.75	0.1888	26.4	5.04	4.80	4E
G.066.063.0825	6.6	0.63	8.25	90	33.75	0.1605	26.4	5.83	4.80	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.066.063.0950	6.6	0.63	9.50	180	33.75	0.1393	26.4	6.62	4.80	4E
G.066.063.1075	6.6	0.63	10.75	270	33.75	0.1231	26.4	7.40	4.80	4E
G.067.070.0200	6.7	0.70	2.00	0	45.83	1.0095	26.8	2.10	4.70	4E
G.067.070.0450	6.7	0.70	4.50	180	45.83	0.4484	26.8	3.85	4.70	4E
G.067.070.0700	6.7	0.70	7.00	0	45.83	0.2882	26.8	5.60	4.70	4E
G.067.070.1075	6.7	0.70	10.75	270	45.83	0.1877	26.8	8.23	4.70	4E
G.067.080.1075	6.7	0.80	10.75	270	92.70	0.3433	26.8	9.40	4.00	4E
G.068.050.0675	6.8	0.50	6.75	270	21.10	0.0781	27.2	3.88	4.40	4E
G.068.070.0325	6.8	0.70	3.25	90	58.20	0.6467	27.2	2.98	4.00	4E
G.069.055.0950	6.9	0.55	9.50	180	24.60	0.0683	27.6	5.78	4.80	4E
G.069.056.0950	6.9	0.56	9.50	180	34.80	0.0967	27.6	5.88	4.40	4E
G.069.075.0700	6.9	0.75	7.00	0	70.60	0.3922	27.6	6.00	4.40	4E
G.069.075.1075	6.9	0.75	10.75	270	70.60	0.2615	27.6	8.81	4.40	4E
G.069.080.0700	6.9	0.80	7.00	0	92.70	0.5150	27.6	6.40	4.00	4E
G.070.050.0350	7.0	0.50	3.50	180	15.78	0.1133	28.0	2.25	4.60	4E
G.070.050.0525	7.0	0.50	5.25	90	15.78	0.0792	28.0	3.13	4.60	4E
G.070.050.0775	7.0	0.50	7.75	270	15.78	0.0554	28.0	4.38	4.60	4E
G.070.050.1200	7.0	0.50	12.00	0	15.78	0.0366	28.0	6.50	4.60	4E
G.070.080.0350	7.0	0.80	3.50	180	58.58	0.7730	28.0	3.60	4.00	4E
G.070.080.0525	7.0	0.80	5.25	90	58.58	0.5414	28.0	5.00	4.00	4E
G.070.080.0775	7.0	0.80	7.75	270	58.58	0.3791	28.0	7.00	4.00	4E
G.070.080.1200	7.0	0.80	12.00	0	58.58	0.2511	28.0	10.40	4.00	4E
G.071.075.0325	7.1	0.75	3.25	90	70.60	0.7844	28.4	3.19	4.40	4E
G.072.055.0675	7.2	0.55	6.75	270	24.60	0.0911	28.8	4.26	4.80	4E
G.073.080.0325	7.3	0.80	3.25	90	92.70	1.0300	29.2	3.40	4.40	4E
G.075.100.0200	7.5	1.00	2.00	0	127.82	3.8733	30.0	3.00	5.00	4I
G.075.100.0225	7.5	1.00	2.25	90	127.82	3.4453	30.0	3.25	5.00	4I
G.075.100.0250	7.5	1.00	2.50	180	127.82	3.1024	30.0	3.50	5.00	4I
G.075.100.0275	7.5	1.00	2.75	270	127.82	2.8216	30.0	3.75	5.00	4I
G.075.100.0300	7.5	1.00	3.00	0	127.82	2.5822	30.0	4.00	5.00	4I
G.075.100.0325	7.5	1.00	3.25	90	127.82	2.3847	30.0	4.25	5.00	4I
G.075.100.0350	7.5	1.00	3.50	180	127.82	2.2153	30.0	4.50	5.00	4I
G.075.100.0375	7.5	1.00	3.75	270	127.82	2.0683	30.0	4.75	5.00	4I
G.075.100.0400	7.5	1.00	4.00	0	127.82	1.9367	30.0	5.00	5.00	4I
G.075.100.0525	7.5	1.00	5.25	90	127.82	1.4760	30.0	6.25	5.00	4I
G.075.100.0650	7.5	1.00	6.50	180	127.82	1.1924	30.0	7.50	5.00	4I
G.075.100.0775	7.5	1.00	7.75	270	127.82	1.0002	30.0	8.75	5.00	4I
G.076.063.0200	7.6	0.63	2.00	0	33.75	0.5672	30.4	1.89	5.70	4E
G.076.063.0325	7.6	0.63	3.25	90	33.75	0.3490	30.4	2.68	5.70	4E
G.076.063.0450	7.6	0.63	4.50	180	33.75	0.2522	30.4	3.47	5.70	4E
G.076.063.0575	7.6	0.63	5.75	270	33.75	0.1974	30.4	4.25	5.70	4E
G.076.063.0700	7.6	0.63	7.00	0	33.75	0.1621	30.4	5.04	5.70	4E
G.076.063.0825	7.6	0.63	8.25	90	33.75	0.1375	30.4	5.83	5.70	4E
G.076.063.0950	7.6	0.63	9.50	180	33.75	0.1195	30.4	6.62	5.70	4E
G.076.063.1075	7.6	0.63	10.75	270	33.75	0.1056	30.4	7.40	5.70	4E
G.076.080.0200	7.6	0.80	2.00	0	67.41	1.5182	30.4	2.40	5.40	4E
G.076.080.0225	7.6	0.80	2.25	90	67.41	1.3509	30.4	2.60	5.40	4E
G.076.080.0250	7.6	0.80	2.50	180	67.41	1.2146	30.4	2.80	5.40	4E
G.076.080.0275	7.6	0.80	2.75	270	67.41	1.1051	30.4	3.00	5.40	4E
G.076.080.0300	7.6	0.80	3.00	0	67.41	1.0122	30.4	3.20	5.40	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.076.080.0325	7.6	0.80	3.25	90	67.41	0.9350	30.4	3.40	5.40	4E
G.076.080.0350	7.6	0.80	3.50	180	67.41	0.8676	30.4	3.60	5.40	4E
G.076.080.0375	7.6	0.80	3.75	270	67.41	0.8102	30.4	3.80	5.40	4E
G.076.080.0400	7.6	0.80	4.00	0	67.41	0.7591	30.4	4.00	5.40	4E
G.076.080.0525	7.6	0.80	5.25	90	67.41	0.5786	30.4	5.00	5.40	4E
G.076.080.0650	7.6	0.80	6.50	180	67.41	0.4672	30.4	6.00	5.40	4E
G.076.080.0775	7.6	0.80	7.75	270	67.41	0.3919	30.4	7.00	5.40	4E
G.077.065.0500	7.7	0.65	5.00	0	42.40	0.2356	30.8	3.90	5.20	4E
G.077.070.0200	7.7	0.70	2.00	0	45.83	0.8647	30.8	2.10	5.60	4E
G.077.070.0325	7.7	0.70	3.25	90	45.83	0.5323	30.8	2.98	5.60	4E
G.077.070.0450	7.7	0.70	4.50	180	45.83	0.3845	30.8	3.85	5.60	4E
G.077.070.0575	7.7	0.70	5.75	270	45.83	0.3007	30.8	4.73	5.60	4E
G.077.070.0700	7.7	0.70	7.00	0	45.83	0.2471	30.8	5.60	5.60	4E
G.077.070.0825	7.7	0.70	8.25	90	45.83	0.2097	30.8	6.48	5.60	4E
G.077.070.0950	7.7	0.70	9.50	180	45.83	0.1821	30.8	7.35	5.60	4E
G.077.070.1075	7.7	0.70	10.75	270	45.83	0.1609	30.8	8.23	5.60	4E
G.077.090.0800	7.7	0.90	8.00	0	113.00	0.6278	30.8	8.10	4.80	4I
G.078.100.0425	7.8	1.00	4.25	90	155.40	1.7267	31.2	5.25	4.80	4I
G.079.090.1075	7.9	0.90	10.75	270	113.00	0.4185	31.6	10.58	4.80	4I
G.080.055.0350	8.0	0.55	3.50	180	21.06	0.1448	32.0	2.48	5.30	4E
G.080.055.0525	8.0	0.55	5.25	90	21.06	0.1012	32.0	3.44	5.30	4E
G.080.055.0775	8.0	0.55	7.75	270	21.06	0.0707	32.0	4.81	5.30	4E
G.080.055.1200	8.0	0.55	12.00	0	21.06	0.0468	32.0	7.15	5.30	4E
G.080.090.0325	8.0	0.90	3.25	90	113.00	1.2556	32.0	3.83	4.80	4I
G.080.090.0350	8.0	0.90	3.50	180	83.58	1.0815	32.0	4.05	4.60	4I
G.080.090.0525	8.0	0.90	5.25	90	83.58	0.7574	32.0	5.63	4.60	4I
G.080.090.0775	8.0	0.90	7.75	270	83.58	0.5303	32.0	7.88	4.60	4I
G.080.090.1200	8.0	0.90	12.00	0	83.58	0.3513	32.0	11.70	4.60	4I
G.082.065.0950	8.2	0.65	9.50	180	42.40	0.1178	32.8	6.83	5.50	4E
G.084.070.0775	8.4	0.70	7.75	270	58.20	0.2156	33.6	6.13	5.20	4E
G.086.065.0675	8.6	0.65	6.75	270	42.40	0.1570	34.4	5.04	5.50	4E
G.086.070.0500	8.6	0.70	5.00	0	58.20	0.3233	34.4	4.20	5.20	4E
G.087.070.0200	8.7	0.70	2.00	0	45.83	0.7563	34.8	2.10	6.50	4E
G.087.070.0325	8.7	0.70	3.25	90	45.83	0.4658	34.8	2.98	6.50	4E
G.087.070.0450	8.7	0.70	4.50	180	45.83	0.3362	34.8	3.85	6.50	4E
G.087.070.0575	8.7	0.70	5.75	270	45.83	0.2632	34.8	4.73	6.50	4E
G.087.070.0700	8.7	0.70	7.00	0	45.83	0.2162	34.8	5.60	6.50	4E
G.087.070.0825	8.7	0.70	8.25	90	45.83	0.1835	34.8	6.48	6.50	4E
G.087.070.0950	8.7	0.70	9.50	180	45.83	0.1593	34.8	7.35	6.50	4E
G.087.070.1075	8.7	0.70	10.75	270	45.83	0.1408	34.8	8.23	6.50	4E
G.088.065.0700	8.8	0.65	7.00	0	26.26	0.1384	35.2	5.20	6.46	4E
G.088.080.0200	8.8	0.80	2.00	0	67.41	1.2914	35.2	2.40	6.50	4E
G.088.080.0225	8.8	0.80	2.25	90	67.41	1.1484	35.2	2.60	6.50	4E
G.088.080.0250	8.8	0.80	2.50	180	67.41	1.0323	35.2	2.80	6.50	4E
G.088.080.0275	8.8	0.80	2.75	270	67.41	0.9389	35.2	3.00	6.50	4E
G.088.080.0300	8.8	0.80	3.00	0	67.41	0.8609	35.2	3.20	6.50	4E
G.088.080.0325	8.8	0.80	3.25	90	67.41	0.7940	35.2	3.40	6.50	4E
G.088.080.0350	8.8	0.80	3.50	180	67.41	0.7375	35.2	3.60	6.50	4E
G.088.080.0375	8.8	0.80	3.75	270	67.41	0.6886	35.2	3.80	6.50	4E
G.088.080.0400	8.8	0.80	4.00	0	67.41	0.6457	35.2	4.00	6.50	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.088.080.0525	8.8	0.80	5.25	90	67.41	0.4917	35.2	5.00	6.50	4E
G.088.080.0650	8.8	0.80	6.50	180	67.41	0.3972	35.2	6.00	6.50	4E
G.088.080.0775	8.8	0.80	7.75	270	67.41	0.3332	35.2	7.00	6.50	4E
G.088.100.0800	8.8	1.00	8.00	0	155.40	0.8633	35.2	9.00	5.50	4I
G.089.130.3075	8.9	1.30	30.75	270	248.00	0.5950	35.6	41.28	5.20	4I
G.090.060.0350	9.0	0.60	3.50	180	27.40	0.1819	36.0	2.70	6.00	4E
G.090.060.0525	9.0	0.60	5.25	90	27.40	0.1271	36.0	3.75	6.00	4E
G.090.060.0775	9.0	0.60	7.75	270	27.40	0.0889	36.0	5.25	6.00	4E
G.090.060.1200	9.0	0.60	12.00	0	27.40	0.0588	36.0	7.80	6.00	4E
G.090.070.0950	9.0	0.70	9.50	180	58.20	0.1617	36.0	7.35	5.50	4E
G.090.080.0775	9.0	0.80	7.75	270	92.70	0.3433	36.0	7.00	5.50	4E
G.090.100.0350	9.0	1.00	3.50	180	114.84	1.4633	36.0	4.50	5.20	4I
G.090.100.0525	9.0	1.00	5.25	90	114.84	1.0247	36.0	6.25	5.20	4I
G.090.100.0775	9.0	1.00	7.75	270	114.84	0.7175	36.0	8.75	5.20	4I
G.090.100.1175	9.0	1.00	11.75	270	134.50	0.4981	36.0	12.75	5.50	4I
G.090.100.1200	9.0	1.00	12.00	0	114.84	0.4752	36.0	13.00	5.20	4I
G.091.100.1175	9.1	1.00	11.75	270	155.40	0.5756	36.4	12.75	5.50	4I
G.091.112.0425	9.1	1.12	4.25	90	226.00	2.5111	36.4	5.88	5.20	4I
G.093.080.0500	9.3	0.80	5.00	0	92.70	0.5150	37.2	4.80	5.50	4E
G.094.100.0700	9.4	1.00	7.00	0	134.50	0.7472	37.6	8.00	5.50	4I
G.095.100.0200	9.5	1.00	2.00	0	127.82	2.9657	38.0	3.00	6.70	4I
G.095.100.0225	9.5	1.00	2.25	90	127.82	2.6355	38.0	3.25	6.70	4I
G.095.100.0250	9.5	1.00	2.50	180	127.82	2.3714	38.0	3.50	6.70	4I
G.095.100.0275	9.5	1.00	2.75	270	127.82	2.1555	38.0	3.75	6.70	4I
G.095.100.0300	9.5	1.00	3.00	0	127.82	1.9756	38.0	4.00	6.70	4I
G.095.100.0325	9.5	1.00	3.25	90	127.82	1.8260	38.0	4.25	6.70	4I
G.095.100.0350	9.5	1.00	3.50	180	127.82	1.6952	38.0	4.50	6.70	4I
G.095.100.0375	9.5	1.00	3.75	270	127.82	1.5819	38.0	4.75	6.70	4I
G.095.100.0400	9.5	1.00	4.00	0	127.82	1.4828	38.0	5.00	6.70	4I
G.095.100.0525	9.5	1.00	5.25	90	127.82	1.1302	38.0	6.25	6.70	4I
G.095.100.0650	9.5	1.00	6.50	180	127.82	0.9123	38.0	7.50	6.70	4I
G.095.100.0775	9.5	1.00	7.75	270	127.82	0.7654	38.0	8.75	6.70	4I
G.095.120.0425	9.5	1.20	4.25	90	282.00	3.1333	38.0	6.30	5.50	4I
G.096.075.0775	9.6	0.75	7.75	270	70.60	0.2615	38.4	6.56	6.40	4E
G.096.112.0800	9.6	1.12	8.00	0	226.00	1.2556	38.4	10.08	5.50	4I
G.097.080.0950	9.7	0.80	9.50	180	92.70	0.2575	38.8	8.40	6.00	4E
G.097.112.1175	9.7	1.12	11.75	270	226.00	0.8370	38.8	14.28	5.90	4I
G.098.100.0325	9.8	1.00	3.25	90	134.50	1.4944	39.2	4.25	5.90	4I
G.098.140.0575	9.8	1.40	5.75	270	358.00	4.2060	39.2	9.45	5.70	4J
G.100.070.0350	10.0	0.70	3.50	180	43.36	0.3042	40.0	3.15	6.60	4E
G.100.070.0525	10.0	0.70	5.25	90	43.36	0.2126	40.0	4.38	6.60	4E
G.100.070.0775	10.0	0.70	7.75	270	43.36	0.1487	40.0	6.13	6.60	4E
G.100.070.1200	10.0	0.70	12.00	0	43.36	0.0984	40.0	9.10	6.60	4E
G.100.075.0500	10.0	0.75	5.00	0	70.60	0.3922	40.0	4.50	6.40	4E
G.100.110.0350	10.0	1.10	3.50	180	144.81	1.9262	40.0	4.95	5.80	4I
G.100.110.0525	10.0	1.10	5.25	90	144.81	1.3487	40.0	6.88	5.80	4I
G.100.110.0775	10.0	1.10	7.75	270	144.81	0.9443	40.0	9.63	5.80	4I
G.100.110.1200	10.0	1.10	12.00	0	144.81	0.6255	40.0	14.30	5.80	4I
G.103.120.0800	10.3	1.20	8.00	0	282.00	1.5667	41.2	10.80	6.40	4I
G.104.075.0950	10.4	0.75	9.50	180	70.60	0.1961	41.6	7.88	6.40	4E

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.104.130.0425	10.4	1.30	4.25	90	328.00	3.6444	41.6	6.83	5.90	4I
G.106.120.1175	10.6	1.20	11.75	270	282.00	1.0444	42.4	15.30	6.40	4I
G.108.080.0200	10.8	0.80	2.00	0	67.41	1.0323	43.2	2.40	8.30	4E
G.108.080.0225	10.8	0.80	2.25	90	67.41	0.9184	43.2	2.60	8.30	4E
G.108.080.0250	10.8	0.80	2.50	180	67.41	0.8261	43.2	2.80	8.30	4E
G.108.080.0275	10.8	0.80	2.75	270	67.41	0.7515	43.2	3.00	8.30	4E
G.108.080.0300	10.8	0.80	3.00	0	67.41	0.6886	43.2	3.20	8.30	4E
G.108.080.0325	10.8	0.80	3.25	90	67.41	0.6359	43.2	3.40	8.30	4E
G.108.080.0350	10.8	0.80	3.50	180	67.41	0.5903	43.2	3.60	8.30	4E
G.108.080.0375	10.8	0.80	3.75	270	67.41	0.5507	43.2	3.80	8.30	4E
G.108.080.0400	10.8	0.80	4.00	0	67.41	0.5166	43.2	4.00	8.30	4E
G.108.080.0525	10.8	0.80	5.25	90	67.41	0.3935	43.2	5.00	8.30	4E
G.108.080.0650	10.8	0.80	6.50	180	67.41	0.3178	43.2	6.00	8.30	4E
G.108.080.0775	10.8	0.80	7.75	270	67.41	0.2665	43.2	7.00	8.30	4E
G.108.130.0675	10.8	1.30	6.75	270	237.00	2.3370	43.2	10.08	6.69	4I
G.109.130.0800	10.9	1.30	8.00	0	328.00	1.8222	43.6	11.70	6.40	4I
G.110.080.0350	11.0	0.80	3.50	180	61.26	0.4730	44.0	3.60	7.30	4E
G.110.080.0525	11.0	0.80	5.25	90	61.26	0.3306	44.0	5.00	7.30	4E
G.110.080.0775	11.0	0.80	7.75	270	61.26	0.2312	44.0	7.00	7.30	4E
G.110.080.1200	11.0	0.80	12.00	0	61.26	0.1530	44.0	10.40	7.30	4E
G.110.090.0775	11.0	0.90	7.75	270	113.00	0.4185	44.0	7.88	7.10	4I
G.110.100.0200	11.0	1.00	2.00	0	127.82	2.5211	44.0	3.00	8.10	4I
G.110.100.0225	11.0	1.00	2.25	90	127.82	2.2425	44.0	3.25	8.10	4I
G.110.100.0250	11.0	1.00	2.50	180	127.82	2.0161	44.0	3.50	8.10	4I
G.110.100.0275	11.0	1.00	2.75	270	127.82	1.8339	44.0	3.75	8.10	4I
G.110.100.0300	11.0	1.00	3.00	0	127.82	1.6818	44.0	4.00	8.10	4I
G.110.100.0325	11.0	1.00	3.25	90	127.82	1.5512	44.0	4.25	8.10	4I
G.110.100.0350	11.0	1.00	3.50	180	127.82	1.4410	44.0	4.50	8.10	4I
G.110.100.0375	11.0	1.00	3.75	270	127.82	1.3441	44.0	4.75	8.10	4I
G.110.100.0400	11.0	1.00	4.00	0	127.82	1.2606	44.0	5.00	8.10	4I
G.110.100.0525	11.0	1.00	5.25	90	127.82	0.9603	44.0	6.25	8.10	4I
G.110.100.0650	11.0	1.00	6.50	180	127.82	0.7756	44.0	7.50	8.10	4I
G.110.100.0775	11.0	1.00	7.75	270	127.82	0.6505	44.0	8.75	8.10	4I
G.110.125.0350	11.0	1.25	3.50	180	211.62	2.9301	44.0	5.63	6.30	4I
G.110.125.0525	11.0	1.25	5.25	90	211.62	2.0521	44.0	7.81	6.30	4I
G.110.125.0775	11.0	1.25	7.75	270	211.62	1.4359	44.0	10.94	6.30	4I
G.110.125.1200	11.0	1.25	12.00	0	211.62	0.9519	44.0	16.25	6.30	4I
G.112.130.1275	11.2	1.30	12.75	270	328.00	1.2148	44.8	17.88	6.80	4I
G.114.090.0500	11.4	0.90	5.00	0	113.00	0.6278	45.6	5.40	7.10	4I
G.118.125.0200	11.8	1.25	2.00	0	242.94	5.8540	47.2	3.75	8.30	4I
G.118.125.0225	11.8	1.25	2.25	90	242.94	5.2133	47.2	4.06	8.30	4I
G.118.125.0250	11.8	1.25	2.50	180	242.94	4.6900	47.2	4.38	8.30	4I
G.118.125.0275	11.8	1.25	2.75	270	242.94	4.2621	47.2	4.69	8.30	4I
G.118.125.0300	11.8	1.25	3.00	0	242.94	3.9058	47.2	5.00	8.30	4I
G.118.125.0325	11.8	1.25	3.25	90	242.94	3.6045	47.2	5.31	8.30	4I
G.118.125.0350	11.8	1.25	3.50	180	242.94	3.3509	47.2	5.63	8.30	4I
G.118.125.0375	11.8	1.25	3.75	270	242.94	3.1266	47.2	5.94	8.30	4I
G.118.125.0400	11.8	1.25	4.00	0	242.94	2.9305	47.2	6.25	8.30	4I
G.118.125.0525	11.8	1.25	5.25	90	242.94	2.2329	47.2	7.81	8.30	4I
G.118.125.0650	11.8	1.25	6.50	180	242.94	1.8036	47.2	9.38	8.30	4I

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.118.125.0775	11.8	1.25	7.75	270	242.94	1.5127	47.2	10.94	8.30	4I
G.120.090.0950	12.0	0.90	9.50	180	113.00	0.3139	48.0	9.45	7.90	4I
G.121.100.0775	12.1	1.00	7.75	270	134.50	0.4981	48.4	8.75	7.90	4I
G.121.160.0200	12.1	1.60	2.00	0	489.79	15.7489	48.4	4.80	8.00	4J
G.121.160.0225	12.1	1.60	2.25	90	489.79	13.9940	48.4	5.20	8.00	4J
G.121.160.0250	12.1	1.60	2.50	180	489.79	12.5910	48.4	5.60	8.00	4J
G.121.160.0275	12.1	1.60	2.75	270	489.79	11.4437	48.4	6.00	8.00	4J
G.121.160.0300	12.1	1.60	3.00	0	489.79	10.4880	48.4	6.40	8.00	4J
G.121.160.0325	12.1	1.60	3.25	90	489.79	9.6796	48.4	6.80	8.00	4J
G.121.160.0350	12.1	1.60	3.50	180	489.79	8.9870	48.4	7.20	8.00	4J
G.121.160.0375	12.1	1.60	3.75	270	489.79	8.3868	48.4	7.60	8.00	4J
G.121.160.0400	12.1	1.60	4.00	0	489.79	7.8618	48.4	8.00	8.00	4J
G.121.160.0525	12.1	1.60	5.25	90	489.79	5.9877	48.4	10.00	8.00	4J
G.121.160.0650	12.1	1.60	6.50	180	489.79	4.8398	48.4	12.00	8.00	4J
G.121.160.0775	12.1	1.60	7.75	270	489.79	4.0579	48.4	14.00	8.00	4J
G.123.140.0425	12.3	1.40	4.25	90	370.00	4.1111	49.2	7.35	7.50	4J
G.124.100.0500	12.4	1.00	5.00	0	134.50	0.7472	49.6	6.00	8.10	4I
G.125.090.0350	12.5	0.90	3.50	180	87.29	0.6663	50.0	4.05	8.30	4I
G.125.090.0525	12.5	0.90	5.25	90	87.29	0.4657	50.0	5.63	8.30	4I
G.125.090.0775	12.5	0.90	7.75	270	87.29	0.3256	50.0	7.88	8.30	4I
G.125.090.1200	12.5	0.90	12.00	0	87.29	0.2155	50.0	11.70	8.30	4I
G.125.140.0350	12.5	1.40	3.50	180	297.87	4.0509	50.0	6.30	7.20	4J
G.125.140.0525	12.5	1.40	5.25	90	297.87	2.8368	50.0	8.75	7.20	4J
G.125.140.0775	12.5	1.40	7.75	270	297.87	1.9863	50.0	12.25	7.20	4J
G.125.140.1200	12.5	1.40	12.00	0	297.87	1.3157	50.0	18.20	7.20	4J
G.127.150.0425	12.7	1.50	4.25	90	475.00	5.2778	50.8	7.88	7.50	4J
G.127.150.0525	12.7	1.50	5.25	90	395.00	4.2700	50.8	9.38	7.84	4J
G.129.100.1050	12.9	1.00	10.50	180	155.40	0.4317	51.6	11.50	8.70	4I
G.129.140.0800	12.9	1.40	8.00	0	370.00	2.0556	51.6	12.60	7.90	4J
G.130.100.0775	13.0	1.00	7.75	270	155.40	0.5756	52.0	8.75	8.70	4I
G.131.100.1050	13.1	1.00	10.50	180	134.50	0.3736	52.4	11.50	8.30	4I
G.131.140.1175	13.1	1.40	11.75	270	370.00	1.3704	52.4	17.85	7.90	4J
G.132.100.0500	13.2	1.00	5.00	0	155.40	0.8633	52.8	6.00	8.70	4I
G.134.150.0800	13.4	1.50	8.00	0	475.00	2.6389	53.6	13.50	8.30	4J
G.135.100.0200	13.5	1.00	2.00	0	127.82	2.0161	54.0	3.00	10.30	4I
G.135.100.0225	13.5	1.00	2.25	90	127.82	1.7927	54.0	3.25	10.30	4I
G.135.100.0250	13.5	1.00	2.50	180	127.82	1.6139	54.0	3.50	10.30	4I
G.135.100.0275	13.5	1.00	2.75	270	127.82	1.4675	54.0	3.75	10.30	4I
G.135.100.0300	13.5	1.00	3.00	0	127.82	1.3455	54.0	4.00	10.30	4I
G.135.100.0325	13.5	1.00	3.25	90	127.82	1.2410	54.0	4.25	10.30	4I
G.135.100.0350	13.5	1.00	3.50	180	127.82	1.1526	54.0	4.50	10.30	4I
G.135.100.0375	13.5	1.00	3.75	270	127.82	1.0752	54.0	4.75	10.30	4I
G.135.100.0400	13.5	1.00	4.00	0	127.82	1.0088	54.0	5.00	10.30	4I
G.135.100.0525	13.5	1.00	5.25	90	127.82	0.7686	54.0	6.25	10.30	4I
G.135.100.0650	13.5	1.00	6.50	180	127.82	0.6208	54.0	7.50	10.30	4I
G.135.100.0775	13.5	1.00	7.75	270	127.82	0.5207	54.0	8.75	10.30	4I
G.136.150.1175	13.6	1.50	11.75	270	399.00	1.7580	54.4	19.13	8.59	4J
G.136.150.1275	13.6	1.50	12.75	270	475.00	1.7593	54.4	20.63	8.30	4J
G.138.125.0200	13.8	1.25	2.00	0	242.94	4.8950	55.2	3.75	10.10	4I
G.138.125.0225	13.8	1.25	2.25	90	242.94	4.3773	55.2	4.06	10.10	4I

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.138.125.0250	13.8	1.25	2.50	180	242.94	3.9374	55.2	4.38	10.10	4I
G.138.125.0275	13.8	1.25	2.75	270	242.94	3.5832	55.2	4.69	10.10	4I
G.138.125.0300	13.8	1.25	3.00	0	242.94	3.2830	55.2	5.00	10.10	4I
G.138.125.0325	13.8	1.25	3.25	90	242.94	3.0292	55.2	5.31	10.10	4I
G.138.125.0350	13.8	1.25	3.50	180	242.94	2.8151	55.2	5.63	10.10	4I
G.138.125.0375	13.8	1.25	3.75	270	242.94	2.6264	55.2	5.94	10.10	4I
G.138.125.0400	13.8	1.25	4.00	0	242.94	2.4614	55.2	6.25	10.10	4I
G.138.125.0525	13.8	1.25	5.25	90	242.94	1.8760	55.2	7.81	10.10	4I
G.138.125.0650	13.8	1.25	6.50	180	242.94	1.5155	55.2	9.38	10.10	4I
G.138.125.0775	13.8	1.25	7.75	270	242.94	1.2706	55.2	10.94	10.10	4I
G.139.112.1050	13.9	1.12	10.50	180	226.00	0.6278	55.6	12.88	9.10	4I
G.140.100.0350	14.0	1.00	3.50	180	119.80	0.9063	56.0	4.50	9.30	4I
G.140.100.0525	14.0	1.00	5.25	90	119.80	0.6334	56.0	6.25	9.30	4I
G.140.100.0775	14.0	1.00	7.75	270	119.80	0.4429	56.0	8.75	9.30	4I
G.140.100.1200	14.0	1.00	12.00	0	119.80	0.2931	56.0	13.00	9.30	4I
G.140.160.0350	14.0	1.60	3.50	180	420.79	6.1839	56.0	7.20	8.00	4J
G.140.160.0525	14.0	1.60	5.25	90	420.79	4.3309	56.0	10.00	8.00	4J
G.140.160.0775	14.0	1.60	7.75	270	420.79	3.0326	56.0	14.00	8.00	4J
G.140.160.1200	14.0	1.60	12.00	0	420.79	2.0090	56.0	20.80	8.00	4J
G.141.112.0775	14.1	1.12	7.75	270	226.00	0.8370	56.4	9.80	9.10	4I
G.141.130.0600	14.1	1.30	6.00	0	328.00	1.8222	56.4	9.10	8.70	4I
G.142.160.0425	14.2	1.60	4.25	90	582.00	6.4667	56.8	8.40	8.70	4J
G.145.130.0875	14.5	1.30	8.75	270	328.00	1.2148	58.0	12.68	9.10	4I
G.146.112.0500	14.6	1.12	5.00	0	226.00	1.2556	58.4	6.72	9.10	4I
G.150.160.0800	15.0	1.60	8.00	0	582.00	3.2333	60.0	14.40	9.10	4J
G.150.200.0200	15.0	2.00	2.00	0	912.63	31.0418	60.0	6.00	9.90	4K
G.150.200.0225	15.0	2.00	2.25	90	912.63	27.5719	60.0	6.50	9.90	4K
G.150.200.0250	15.0	2.00	2.50	180	912.63	24.7997	60.0	7.00	9.90	4K
G.150.200.0275	15.0	2.00	2.75	270	912.63	22.5341	60.0	7.50	9.90	4K
G.150.200.0300	15.0	2.00	3.00	0	912.63	20.6946	60.0	8.00	9.90	4K
G.150.200.0325	15.0	2.00	3.25	90	912.63	19.0927	60.0	8.50	9.90	4K
G.150.200.0350	15.0	2.00	3.50	180	912.63	17.7210	60.0	9.00	9.90	4K
G.150.200.0375	15.0	2.00	3.75	270	912.63	16.5332	60.0	9.50	9.90	4K
G.150.200.0400	15.0	2.00	4.00	0	912.63	15.4946	60.0	10.00	9.90	4K
G.150.200.0525	15.0	2.00	5.25	90	912.63	11.8063	60.0	12.50	9.90	4K
G.150.200.0650	15.0	2.00	6.50	180	912.63	9.5463	60.0	15.00	9.90	4K
G.150.200.0775	15.0	2.00	7.75	270	912.63	8.0055	60.0	17.50	9.90	4K
G.150.250.0200	15.0	2.50	2.00	0	1696.59	78.5458	60.0	7.50	9.00	4L
G.150.250.0325	15.0	2.50	3.25	90	1696.59	48.4740	60.0	10.63	9.00	4L
G.150.250.0450	15.0	2.50	4.50	180	1696.59	34.9812	60.0	13.75	9.00	4L
G.150.250.0575	15.0	2.50	5.75	270	1696.59	27.3644	60.0	16.88	9.00	4L
G.150.250.0700	15.0	2.50	7.00	0	1696.59	22.4714	60.0	20.00	9.00	4L
G.150.250.0825	15.0	2.50	8.25	90	1696.59	19.0628	60.0	23.13	9.00	4L
G.150.250.0950	15.0	2.50	9.50	180	1696.59	16.5683	60.0	26.25	9.00	4L
G.150.250.1075	15.0	2.50	10.75	270	1696.59	14.6384	60.0	29.38	9.00	4L
G.151.120.1050	15.1	1.20	10.50	180	282.00	0.7833	60.4	13.80	10.30	4I
G.151.160.0200	15.1	1.60	2.00	0	489.79	12.2448	60.4	4.80	10.70	4J
G.151.160.0225	15.1	1.60	2.25	90	489.79	10.8842	60.4	5.20	10.70	4J
G.151.160.0250	15.1	1.60	2.50	180	489.79	9.7958	60.4	5.60	10.70	4J
G.151.160.0275	15.1	1.60	2.75	270	489.79	8.9053	60.4	6.00	10.70	4J

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.151.160.0300	15.1	1.60	3.00	0	489.79	8.1632	60.4	6.40	10.70	4J
G.151.160.0325	15.1	1.60	3.25	90	489.79	7.5352	60.4	6.80	10.70	4J
G.151.160.0350	15.1	1.60	3.50	180	489.79	6.9970	60.4	7.20	10.70	4J
G.151.160.0375	15.1	1.60	3.75	270	489.79	6.5305	60.4	7.60	10.70	4J
G.151.160.0400	15.1	1.60	4.00	0	489.79	6.1224	60.4	8.00	10.70	4J
G.151.160.0525	15.1	1.60	5.25	90	489.79	4.6602	60.4	10.00	10.70	4J
G.151.160.0650	15.1	1.60	6.50	180	489.79	3.7647	60.4	12.00	10.70	4J
G.151.160.0775	15.1	1.60	7.75	270	489.79	3.1579	60.4	14.00	10.70	4J
G.151.180.0425	15.1	1.80	4.25	90	791.00	8.7889	60.4	9.45	9.10	4J
G.152.120.0775	15.2	1.20	7.75	270	282.00	1.0444	60.8	10.50	10.30	4I
G.152.160.1175	15.2	1.60	11.75	270	582.00	2.1556	60.8	20.40	9.50	4J
G.157.120.0500	15.7	1.20	5.00	0	282.00	1.5667	62.8	7.20	10.30	4I
G.159.180.0800	15.9	1.80	8.00	0	791.00	4.3944	63.6	16.20	9.90	4J
G.160.110.0350	16.0	1.10	3.50	180	151.29	1.1581	64.0	4.95	10.70	4I
G.160.110.0525	16.0	1.10	5.25	90	151.29	0.8093	64.0	6.88	10.70	4I
G.160.110.0775	16.0	1.10	7.75	270	151.29	0.6669	64.0	9.63	10.70	4I
G.160.110.1200	16.0	1.10	12.00	0	151.29	0.3744	64.0	14.30	10.70	4I
G.160.130.1150	16.0	1.30	11.50	180	328.00	0.9111	64.0	16.25	10.30	4I
G.160.180.0350	16.0	1.80	3.50	180	600.36	8.6523	64.0	8.10	9.20	4J
G.160.180.0525	16.0	1.80	5.25	90	600.36	8.0592	64.0	11.25	9.20	4J
G.160.180.0775	16.0	1.80	7.75	270	600.36	4.2427	64.0	15.75	9.20	4J
G.160.180.1200	16.0	1.80	12.00	0	600.36	2.8104	64.0	23.40	9.20	4J
G.161.190.0425	16.1	1.90	4.25	90	989.00	10.9889	64.4	9.98	9.50	4J
G.162.180.1275	16.2	1.80	12.75	270	791.00	2.9296	64.8	24.75	9.90	4J
G.166.140.0600	16.6	1.40	6.00	0	370.00	2.0556	66.4	9.80	10.70	4J
G.166.140.0875	16.6	1.40	8.75	270	370.00	1.3704	66.4	13.65	11.10	4J
G.166.140.1150	16.6	1.40	11.50	180	370.00	1.0278	66.4	17.50	11.50	4J
G.167.160.0850	16.7	1.60	8.50	180	492.00	2.5350	66.8	15.20	10.80	4J
G.168.125.0200	16.8	1.25	2.00	0	242.94	3.9696	67.2	3.75	12.80	4I
G.168.125.0225	16.8	1.25	2.25	90	242.94	3.5311	67.2	4.06	12.80	4I
G.168.125.0250	16.8	1.25	2.50	180	242.94	3.1757	67.2	4.38	12.80	4I
G.168.125.0275	16.8	1.25	2.75	270	242.94	2.8887	67.2	4.69	12.80	4I
G.168.125.0300	16.8	1.25	3.00	0	242.94	2.6493	67.2	5.00	12.80	4I
G.168.125.0325	16.8	1.25	3.25	90	242.94	2.4441	67.2	5.31	12.80	4I
G.168.125.0350	16.8	1.25	3.50	180	242.94	2.2705	67.2	5.63	12.80	4I
G.168.125.0375	16.8	1.25	3.75	270	242.94	2.1180	67.2	5.94	12.80	4I
G.168.125.0400	16.8	1.25	4.00	0	242.94	1.9864	67.2	6.25	12.80	4I
G.168.125.0525	16.8	1.25	5.25	90	242.94	1.5127	67.2	7.81	12.80	4I
G.168.125.0650	16.8	1.25	6.50	180	242.94	1.2220	67.2	9.38	12.80	4I
G.168.125.0775	16.8	1.25	7.75	270	242.94	1.0251	67.2	10.94	12.80	4I
G.172.190.0800	17.2	1.90	8.00	0	989.00	5.4944	68.8	17.10	10.70	4J
G.172.200.0425	17.2	2.00	4.25	90	1102.00	12.2444	68.8	10.50	10.30	4K
G.173.150.0600	17.3	1.50	6.00	0	475.00	2.6389	69.2	10.50	11.10	4J
G.176.160.0200	17.6	1.60	2.00	0	489.79	10.3331	70.4	4.80	13.00	4J
G.176.160.0225	17.6	1.60	2.25	90	489.79	9.1721	70.4	5.20	13.00	4J
G.176.160.0250	17.6	1.60	2.50	180	489.79	8.2595	70.4	5.60	13.00	4J
G.176.160.0275	17.6	1.60	2.75	270	489.79	7.5121	70.4	6.00	13.00	4J
G.176.160.0300	17.6	1.60	3.00	0	489.79	6.8887	70.4	6.40	13.00	4J
G.176.160.0325	17.6	1.60	3.25	90	489.79	6.3527	70.4	6.80	13.00	4J
G.176.160.0350	17.6	1.60	3.50	180	489.79	5.9011	70.4	7.20	13.00	4J

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.176.160.0375	17.6	1.60	3.75	270	489.79	5.5094	70.4	7.60	13.00	4J
G.176.160.0400	17.6	1.60	4.00	0	489.79	5.1611	70.4	8.00	13.00	4J
G.176.160.0525	17.6	1.60	5.25	90	489.79	3.9341	70.4	10.00	13.00	4J
G.176.160.0650	17.6	1.60	6.50	180	489.79	3.1784	70.4	12.00	13.00	4J
G.176.160.0775	17.6	1.60	7.75	270	489.79	2.6648	70.4	14.00	13.00	4J
G.178.150.0875	17.8	1.50	8.75	270	475.00	1.7593	71.2	14.63	11.50	4J
G.178.190.1175	17.8	1.90	11.75	270	989.00	3.6630	71.2	24.23	12.70	4J
G.180.125.0350	18.0	1.25	3.50	180	221.85	1.7177	72.0	5.63	12.00	4I
G.180.125.0525	18.0	1.25	5.25	90	221.85	1.2004	72.0	7.81	12.00	4I
G.180.125.0775	18.0	1.25	7.75	270	221.85	0.8393	72.0	10.94	12.00	4I
G.180.125.1200	18.0	1.25	12.00	0	221.85	0.5553	72.0	16.25	12.00	4I
G.180.150.1150	18.0	1.50	11.50	180	409.00	1.3180	72.0	18.75	11.87	4J
G.180.150.1250	18.0	1.50	12.50	180	475.00	1.3194	72.0	20.25	11.70	4J
G.180.200.0350	18.0	2.00	3.50	180	824.84	11.7066	72.0	9.00	10.50	4K
G.180.200.0525	18.0	2.00	5.25	90	824.84	8.1976	72.0	12.50	10.50	4K
G.180.200.0775	18.0	2.00	7.75	270	824.84	5.7397	72.0	17.50	10.50	4K
G.180.200.1200	18.0	2.00	12.00	0	824.84	3.8019	72.0	26.00	10.50	4K
G.180.300.0200	18.0	3.00	2.00	0	2820.37	136.2498	72.0	9.00	10.80	4L
G.180.300.0325	18.0	3.00	3.25	90	2820.37	83.6905	72.0	12.75	10.80	4L
G.180.300.0450	18.0	3.00	4.50	180	2820.37	60.3934	72.0	16.50	10.80	4L
G.180.300.0575	18.0	3.00	5.75	270	2820.37	47.3216	72.0	20.25	10.80	4L
G.180.300.0700	18.0	3.00	7.00	0	2820.37	38.8481	72.0	24.00	10.80	4L
G.180.300.0825	18.0	3.00	8.25	90	2820.37	32.9482	72.0	27.75	10.80	4L
G.180.300.0950	18.0	3.00	9.50	180	2820.37	28.6332	72.0	31.50	10.80	4L
G.180.300.1075	18.0	3.00	10.75	270	2820.37	25.2948	72.0	35.25	10.80	4L
G.182.220.0425	18.2	2.20	4.25	90	1356.00	15.0667	72.8	11.55	10.70	4K
G.185.200.0800	18.5	2.00	8.00	0	1102.00	6.1222	74.0	18.00	11.50	4K
G.185.200.1175	18.5	2.00	11.75	270	1102.00	4.0815	74.0	25.50	11.50	4K
G.185.200.1200	18.5	2.00	12.00	0	824.84	3.6796	74.0	26.00	12.77	4K
G.185.250.0200	18.5	2.50	2.00	0	1696.59	61.4707	74.0	7.50	12.10	4L
G.185.250.0325	18.5	2.50	3.25	90	1696.59	37.8703	74.0	10.63	12.10	4L
G.185.250.0450	18.5	2.50	4.50	180	1696.59	27.3203	74.0	13.75	12.10	4L
G.185.250.0575	18.5	2.50	5.75	270	1696.59	21.3946	74.0	16.88	12.10	4L
G.185.250.0700	18.5	2.50	7.00	0	1696.59	17.5812	74.0	20.00	12.10	4L
G.185.250.0825	18.5	2.50	8.25	90	1696.59	14.9479	74.0	23.13	12.10	4L
G.185.250.0950	18.5	2.50	9.50	180	1696.59	14.0214	74.0	26.25	12.10	4L
G.185.250.1075	18.5	2.50	10.75	270	1696.59	11.4403	74.0	29.38	12.10	4L
G.190.200.0200	19.0	2.00	2.00	0	912.63	23.7047	76.0	6.00	13.50	4K
G.190.200.0225	19.0	2.00	2.25	90	912.63	21.0769	76.0	6.50	13.50	4K
G.190.200.0250	19.0	2.00	2.50	180	912.63	18.9736	76.0	7.00	13.50	4K
G.190.200.0275	19.0	2.00	2.75	270	912.63	17.2520	76.0	7.50	13.50	4K
G.190.200.0300	19.0	2.00	3.00	0	912.63	15.8168	76.0	8.00	13.50	4K
G.190.200.0325	19.0	2.00	3.25	90	912.63	14.6021	76.0	8.50	13.50	4K
G.190.200.0350	19.0	2.00	3.50	180	912.63	13.5606	76.0	9.00	13.50	4K
G.190.200.0375	19.0	2.00	3.75	270	912.63	12.6578	76.0	9.50	13.50	4K
G.190.200.0400	19.0	2.00	4.00	0	912.63	11.8678	76.0	10.00	13.50	4K
G.190.200.0650	19.0	2.00	6.50	180	912.63	7.3010	76.0	15.00	13.50	4K
G.190.200.0775	19.0	2.00	7.75	270	912.63	6.1209	76.0	17.50	13.50	4K
G.193.220.0900	19.3	2.20	9.00	0	1356.00	7.5333	77.2	22.00	11.90	4K
G.195.160.0500	19.5	1.60	5.00	0	499.00	3.6430	78.0	9.60	12.86	4J

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.195.160.0600	19.5	1.60	6.00	0	582.00	3.2333	78.0	11.20	12.70	4J
G.196.360.0200	19.6	3.60	2.00	0	4777.41	263.9453	78.4	10.80	11.10	4L
G.196.360.0325	19.6	3.60	3.25	90	4777.41	162.4969	78.4	15.30	11.10	4L
G.196.360.0450	19.6	3.60	4.50	180	4777.41	117.3811	78.4	19.80	11.10	4L
G.196.360.0575	19.6	3.60	5.75	270	4777.41	91.8733	78.4	24.30	11.10	4L
G.196.360.0700	19.6	3.60	7.00	0	4777.41	75.4725	78.4	28.80	11.10	4L
G.196.360.0825	19.6	3.60	8.25	90	4777.41	64.0403	78.4	33.30	11.10	4L
G.196.360.0950	19.6	3.60	9.50	180	4777.41	55.6159	78.4	37.80	11.10	4L
G.196.360.1075	19.6	3.60	10.75	270	4777.41	49.1503	78.4	42.30	11.10	4L
G.197.190.0700	19.7	1.90	7.00	0	989.00	5.4944	78.8	15.20	12.30	4J
G.197.240.0525	19.7	2.40	5.25	90	1808.00	20.0889	78.8	15.00	11.50	4K
G.199.160.0875	19.9	1.60	8.75	270	582.00	2.1556	79.6	15.60	13.10	4J
G.200.140.0350	20.0	1.40	3.50	180	311.51	2.4338	80.0	6.30	13.30	4J
G.200.140.0525	20.0	1.40	5.25	90	311.51	1.7009	80.0	8.75	13.30	4J
G.200.140.0775	20.0	1.40	7.75	270	311.51	1.1893	80.0	12.25	13.30	4J
G.200.140.1200	20.0	1.40	12.00	0	311.51	0.7869	80.0	18.20	13.30	4J
G.200.220.0350	20.0	2.20	3.50	180	1033.42	15.4093	80.0	9.90	11.70	4K
G.200.220.0525	20.0	2.20	5.25	90	1033.42	10.7898	80.0	13.75	11.70	4K
G.200.220.0775	20.0	2.20	7.75	270	1033.42	7.5545	80.0	19.25	11.70	4K
G.200.220.1200	20.0	2.20	12.00	0	1033.42	5.0038	80.0	28.60	11.70	4K
G.201.220.1275	20.1	2.20	12.75	270	1356.00	5.0222	80.4	30.25	12.70	4K
G.203.160.1150	20.3	1.60	11.50	180	582.00	1.6167	81.2	20.00	13.10	4J
G.204.200.0700	20.4	2.00	7.00	0	1102.00	6.1222	81.6	16.00	12.70	4K
G.206.180.0600	20.6	1.80	6.00	0	791.00	4.3944	82.4	12.60	13.10	4J
G.210.180.0875	21.0	1.80	8.75	270	791.00	2.9296	84.0	17.55	13.50	4J
G.210.190.0975	21.0	1.90	9.75	270	989.00	3.6630	84.0	20.43	13.50	4J
G.214.180.1250	21.4	1.80	12.50	180	791.00	2.1972	85.6	24.30	13.90	4J
G.215.270.0525	21.5	2.70	5.25	90	2373.00	26.3667	86.0	16.88	12.70	4L
G.216.160.0200	21.6	1.60	2.00	0	489.79	8.2595	86.4	4.80	16.50	4J
G.216.160.0225	21.6	1.60	2.25	90	489.79	7.3432	86.4	5.20	16.50	4J
G.216.160.0250	21.6	1.60	2.50	180	489.79	6.6099	86.4	5.60	16.50	4J
G.216.160.0275	21.6	1.60	2.75	270	489.79	6.0097	86.4	6.00	16.50	4J
G.216.160.0300	21.6	1.60	3.00	0	489.79	5.5094	86.4	6.40	16.50	4J
G.216.160.0325	21.6	1.60	3.25	90	489.79	5.0861	86.4	6.80	16.50	4J
G.216.160.0350	21.6	1.60	3.50	180	489.79	4.7231	86.4	7.20	16.50	4J
G.216.160.0375	21.6	1.60	3.75	270	489.79	4.4086	86.4	7.60	16.50	4J
G.216.160.0400	21.6	1.60	4.00	0	489.79	4.1332	86.4	8.00	16.50	4J
G.216.160.0525	21.6	1.60	5.25	90	489.79	3.1478	86.4	10.00	16.50	4J
G.216.160.0650	21.6	1.60	6.50	180	489.79	2.5430	86.4	12.00	16.50	4J
G.216.160.0775	21.6	1.60	7.75	270	489.79	2.1323	86.4	14.00	16.50	4J
G.217.200.0975	21.7	2.00	9.75	270	1102.00	4.0815	86.8	21.50	13.90	4K
G.220.160.0350	22.0	1.60	3.50	180	440.02	3.7841	88.0	7.20	14.60	4J
G.220.160.0525	22.0	1.60	5.25	90	440.02	2.6449	88.0	10.00	14.60	4J
G.220.160.0775	22.0	1.60	7.75	270	440.02	1.8495	88.0	14.00	14.60	4J
G.220.160.1200	22.0	1.60	12.00	0	440.02	1.2238	88.0	20.80	14.60	4J
G.220.200.0200	22.0	2.00	2.00	0	912.63	20.1909	88.0	6.00	16.20	4K
G.220.200.0225	22.0	2.00	2.25	90	912.63	17.9299	88.0	6.50	16.20	4K
G.220.200.0250	22.0	2.00	2.50	180	912.63	16.1242	88.0	7.00	16.20	4K
G.220.200.0275	22.0	2.00	2.75	270	912.63	14.6725	88.0	7.50	16.20	4K
G.220.200.0300	22.0	2.00	3.00	0	912.63	13.4408	88.0	8.00	16.20	4K

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.220.200.0325	22.0	2.00	3.25	90	912.63	12.4167	88.0	8.50	16.20	4K
G.220.200.0350	22.0	2.00	3.50	180	912.63	11.5231	88.0	9.00	16.20	4K
G.220.200.0375	22.0	2.00	3.75	270	912.63	10.7621	88.0	9.50	16.20	4K
G.220.200.0400	22.0	2.00	4.00	0	912.63	10.0843	88.0	10.00	16.20	4K
G.220.200.0525	22.0	2.00	5.25	90	912.63	7.6821	88.0	12.50	16.20	4K
G.220.200.0650	22.0	2.00	6.50	180	912.63	6.2041	88.0	15.00	16.20	4K
G.220.200.0775	22.0	2.00	7.75	270	912.63	5.2061	88.0	17.50	16.20	4K
G.220.250.0350	22.0	2.50	3.50	180	1510.19	23.4409	88.0	11.25	12.70	4L
G.220.250.0525	22.0	2.50	5.25	90	1510.19	16.4166	88.0	15.63	12.70	4L
G.220.250.0775	22.0	2.50	7.75	270	1510.19	11.4955	88.0	21.88	12.70	4L
G.220.250.1200	22.0	2.50	12.00	0	1510.19	7.6150	88.0	32.50	12.70	4L
G.220.300.0200	22.0	3.00	2.00	0	2820.37	107.2384	88.0	9.00	14.40	4L
G.220.300.0325	22.0	3.00	3.25	90	2820.37	66.0508	88.0	12.75	14.40	4L
G.220.300.0450	22.0	3.00	4.50	180	2820.37	47.7220	88.0	16.50	14.40	4L
G.220.300.0575	22.0	3.00	5.75	270	2820.37	37.3559	88.0	20.25	14.40	4L
G.220.300.0700	22.0	3.00	7.00	0	2820.37	30.6896	88.0	24.00	14.40	4L
G.220.300.0825	22.0	3.00	8.25	90	2820.37	26.0422	88.0	27.75	14.40	4L
G.220.300.0950	22.0	3.00	9.50	180	2820.37	22.6172	88.0	31.50	14.40	4L
G.220.300.1075	22.0	3.00	10.75	270	2820.37	19.9884	88.0	35.25	14.40	4L
G.221.160.0875	22.1	1.60	8.75	270	504.00	2.1560	88.4	15.60	14.97	4J
G.221.240.0900	22.1	2.40	9.00	0	1808.00	10.0444	88.4	24.00	13.50	4K
G.225.250.0200	22.5	2.50	2.00	0	1696.59	49.1765	90.0	7.50	15.70	4L
G.225.250.0325	22.5	2.50	3.25	90	1696.59	30.2963	90.0	10.63	15.70	4L
G.225.250.0450	22.5	2.50	4.50	180	1696.59	21.8915	90.0	13.75	15.70	4L
G.225.250.0575	22.5	2.50	5.75	270	1696.59	17.1200	90.0	16.88	15.70	4L
G.225.250.0700	22.5	2.50	7.00	0	1696.59	14.0679	90.0	20.00	15.70	4L
G.225.250.0825	22.5	2.50	8.25	90	1696.59	11.9310	90.0	23.13	15.70	4L
G.225.250.0950	22.5	2.50	9.50	180	1696.59	10.3640	90.0	26.25	15.70	4L
G.225.250.1075	22.5	2.50	10.75	270	1696.59	9.1609	90.0	29.38	15.70	4L
G.229.200.1250	22.9	2.00	12.50	180	1102.00	3.0611	91.6	27.00	14.70	4K
G.235.240.1275	23.5	2.40	12.75	270	1808.00	6.6963	94.0	33.00	14.70	4K
G.246.360.0200	24.6	3.60	2.00	0	4777.41	201.5785	98.4	10.80	15.60	4L
G.246.360.0325	24.6	3.60	3.25	90	4777.41	124.0886	98.4	15.30	15.60	4L
G.246.360.0450	24.6	3.60	4.50	180	4777.41	89.4646	98.4	19.80	15.60	4L
G.246.360.0575	24.6	3.60	5.75	270	4777.41	70.0500	98.4	24.30	15.60	4L
G.246.360.0700	24.6	3.60	7.00	0	4777.41	57.5592	98.4	28.80	15.60	4L
G.246.360.0825	24.6	3.60	8.25	90	4777.41	48.8488	98.4	33.30	15.60	4L
G.246.360.0950	24.6	3.60	9.50	180	4777.41	42.4282	98.4	37.80	15.60	4L
G.246.360.1075	24.6	3.60	10.75	270	4777.41	37.4699	98.4	42.30	15.60	4L
G.248.190.1050	24.8	1.90	10.50	180	989.00	2.7472	99.2	21.85	16.30	4J
G.248.290.0525	24.8	2.90	5.25	90	3164.00	35.1556	99.2	18.13	15.10	4L
G.249.270.0900	24.9	2.70	9.00	0	2373.00	13.1833	99.6	27.00	15.50	4L
G.250.180.0350	25.0	1.80	3.50	180	626.96	5.3304	100.0	8.10	16.70	4J
G.250.180.0525	25.0	1.80	5.25	90	626.96	3.7256	100.0	11.25	16.70	4J
G.250.180.0775	25.0	1.80	7.75	270	626.96	2.6051	100.0	15.75	16.70	4J
G.250.180.1200	25.0	1.80	12.00	0	626.96	1.7238	100.0	23.40	16.70	4J
G.250.280.0350	25.0	2.80	3.50	180	2125.68	32.4076	100.0	12.60	14.50	4L
G.250.280.0525	25.0	2.80	5.25	90	2125.68	22.6945	100.0	17.50	14.50	4L
G.250.280.0775	25.0	2.80	7.75	270	2125.68	15.8906	100.0	24.50	14.50	4L
G.250.280.1200	25.0	2.80	12.00	0	2125.68	10.5259	100.0	36.40	14.50	4L

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.251.320.0625	25.1	3.20	6.25	90	3616.00	40.1778	100.4	23.20	15.00	4L
G.252.220.0600	25.2	2.20	6.00	0	1356.00	7.5333	100.8	15.40	16.30	4K
G.255.400.0200	25.5	4.00	2.00	0	6165.41	285.4356	102.0	12.00	15.70	4N
G.255.400.0325	25.5	4.00	3.25	90	6165.41	176.1546	102.0	17.00	15.70	4N
G.255.400.0450	25.5	4.00	4.50	180	6165.41	127.1219	102.0	22.00	15.70	4N
G.255.400.0575	25.5	4.00	5.75	270	6165.41	99.4421	102.0	27.00	15.70	4N
G.255.400.0700	25.5	4.00	7.00	0	6165.41	81.6611	102.0	32.00	15.70	4N
G.255.400.0825	25.5	4.00	8.25	90	6165.41	69.3522	102.0	37.00	15.70	4N
G.255.400.0950	25.5	4.00	9.50	180	6165.41	60.2091	102.0	42.00	15.70	4N
G.255.400.1075	25.5	4.00	10.75	270	6165.41	53.1959	102.0	47.00	15.70	4N
G.264.220.0875	26.4	2.20	8.75	270	1356.00	5.0222	105.6	21.45	17.10	4K
G.265.290.0900	26.5	2.90	9.00	0	3164.00	17.5778	106.0	29.00	16.30	4L
G.268.220.1250	26.8	2.20	12.50	180	1356.00	3.7667	107.2	29.70	17.50	4K
G.270.200.0200	27.0	2.00	2.00	0	912.63	16.1527	108.0	6.00	20.70	4K
G.270.200.0225	27.0	2.00	2.25	90	912.63	14.3495	108.0	6.50	20.70	4K
G.270.200.0250	27.0	2.00	2.50	180	912.63	12.9085	108.0	7.00	20.70	4K
G.270.200.0275	27.0	2.00	2.75	270	912.63	11.7305	108.0	7.50	20.70	4K
G.270.200.0300	27.0	2.00	3.00	0	912.63	10.7621	108.0	8.00	20.70	4K
G.270.200.0325	27.0	2.00	3.25	90	912.63	9.9307	108.0	8.50	20.70	4K
G.270.200.0350	27.0	2.00	3.50	180	912.63	9.2185	108.0	9.00	20.70	4K
G.270.200.0375	27.0	2.00	3.75	270	912.63	8.6097	108.0	9.50	20.70	4K
G.270.200.0400	27.0	2.00	4.00	0	912.63	8.0692	108.0	10.00	20.70	4K
G.270.200.0525	27.0	2.00	5.25	90	912.63	6.1498	108.0	12.50	20.70	4K
G.270.200.0650	27.0	2.00	6.50	180	912.63	4.9653	108.0	15.00	20.70	4K
G.270.200.0775	27.0	2.00	7.75	270	912.63	4.1654	108.0	17.50	20.70	4K
G.270.300.0200	27.0	3.00	2.00	0	2820.37	84.9509	108.0	9.00	18.90	4L
G.270.300.0325	27.0	3.00	3.25	90	2820.37	52.3260	108.0	12.75	18.90	4L
G.270.300.0450	27.0	3.00	4.50	180	2820.37	37.8066	108.0	16.50	18.90	4L
G.270.300.0575	27.0	3.00	5.75	270	2820.37	29.5946	108.0	20.25	18.90	4L
G.270.300.0700	27.0	3.00	7.00	0	2820.37	24.3135	108.0	24.00	18.90	4L
G.270.300.0825	27.0	3.00	8.25	90	2820.37	20.6167	108.0	27.75	18.90	4L
G.270.300.0950	27.0	3.00	9.50	180	2820.37	17.9071	108.0	31.50	18.90	4L
G.270.300.1075	27.0	3.00	10.75	270	2820.37	15.8270	108.0	35.25	18.90	4L
G.275.250.0200	27.5	2.50	2.00	0	1696.59	39.3640	110.0	7.50	20.20	4L
G.275.250.0325	27.5	2.50	3.25	90	1696.59	24.2370	110.0	10.63	20.20	4L
G.275.250.0450	27.5	2.50	4.50	180	1696.59	17.5087	110.0	13.75	20.20	4L
G.275.250.0575	27.5	2.50	5.75	270	1696.59	13.7043	110.0	16.88	20.20	4L
G.275.250.0700	27.5	2.50	7.00	0	1696.59	11.2581	110.0	20.00	20.20	4L
G.275.250.0825	27.5	2.50	8.25	90	1696.59	9.5529	110.0	23.13	20.20	4L
G.275.250.0950	27.5	2.50	9.50	180	1696.59	8.2922	110.0	26.25	20.20	4L
G.275.250.1075	27.5	2.50	10.75	270	1696.59	7.3287	110.0	29.38	20.20	4L
G.275.320.1100	27.5	3.20	11.00	0	3616.00	20.0889	110.0	38.40	16.90	4L
G.276.290.1275	27.6	2.90	12.75	270	3164.00	11.7185	110.4	39.88	17.50	4L
G.277.270.1175	27.7	2.70	11.75	270	2373.00	8.7889	110.8	34.43	17.90	4L
G.280.200.0350	28.0	2.00	3.50	180	860.53	7.2501	112.0	9.00	18.70	4K
G.280.200.0525	28.0	2.00	5.25	90	860.53	5.0672	112.0	12.50	18.70	4K
G.280.200.0775	28.0	2.00	7.75	270	860.53	3.5432	112.0	17.50	18.70	4K
G.280.200.1200	28.0	2.00	12.00	0	860.53	2.3445	112.0	26.00	18.70	4K
G.280.320.0350	28.0	3.20	3.50	180	2963.17	49.4709	112.0	14.40	16.20	4L
G.280.320.0525	28.0	3.20	5.25	90	2963.17	34.6475	112.0	20.00	16.20	4L

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.280.320.0775	28.0	3.20	7.75	270	2963.17	24.2621	112.0	28.00	16.20	4L
G.280.320.1200	28.0	3.20	12.00	0	2963.17	16.0722	112.0	41.60	16.20	4L
G.280.340.0625	28.0	3.40	6.25	90	4519.00	50.2111	112.0	24.65	16.90	4L
G.287.240.0700	28.7	2.40	7.00	0	1808.00	10.0444	114.8	19.20	18.60	4K
G.296.360.0200	29.6	3.60	2.00	0	4777.41	163.0515	118.4	10.80	20.10	4L
G.296.360.0325	29.6	3.60	3.25	90	4777.41	100.1553	118.4	15.30	20.10	4L
G.296.360.0450	29.6	3.60	4.50	180	4777.41	72.3850	118.4	19.80	20.10	4L
G.296.360.0575	29.6	3.60	5.75	270	4777.41	56.6044	118.4	24.30	20.10	4L
G.296.360.0700	29.6	3.60	7.00	0	4777.41	46.5181	118.4	28.80	20.10	4L
G.296.360.0825	29.6	3.60	8.25	90	4777.41	39.4827	118.4	33.30	20.10	4L
G.296.360.0950	29.6	3.60	9.50	180	4777.41	34.2712	118.4	37.80	20.10	4L
G.296.360.1075	29.6	3.60	10.75	270	4777.41	30.2943	118.4	42.30	20.10	4L
G.302.320.1475	30.2	3.20	14.75	270	3616.00	13.3926	120.8	50.40	19.10	4L
G.302.340.1100	30.2	3.40	11.00	0	4519.00	25.1056	120.8	40.80	18.70	4L
G.305.400.0200	30.5	4.00	2.00	0	6165.41	231.7823	122.0	12.00	20.20	4N
G.305.400.0325	30.5	4.00	3.25	90	6165.41	142.7178	122.0	17.00	20.20	4N
G.305.400.0450	30.5	4.00	4.50	180	6165.41	103.1005	122.0	22.00	20.20	4N
G.305.400.0575	30.5	4.00	5.75	270	6165.41	80.6991	122.0	27.00	20.20	4N
G.305.400.0700	30.5	4.00	7.00	0	6165.41	66.2947	122.0	32.00	20.20	4N
G.305.400.0825	30.5	4.00	8.25	90	6165.41	56.2537	122.0	37.00	20.20	4N
G.305.400.0950	30.5	4.00	9.50	180	6165.41	48.8543	122.0	42.00	20.20	4N
G.305.400.1075	30.5	4.00	10.75	270	6165.41	43.1751	122.0	47.00	20.20	4N
G.306.240.0875	30.6	2.40	8.75	270	1808.00	6.6963	122.4	23.40	20.20	4K
G.311.240.1250	31.1	2.40	12.50	180	1808.00	5.0222	124.4	32.40	20.60	4K
G.312.130.0350	31.2	1.30	3.50	180	315.00	1.4330	124.8	5.85	20.68	4I
G.317.270.0700	31.7	2.70	7.00	0	2373.00	13.1833	126.8	21.60	20.60	4L
G.320.300.0200	32.0	3.00	2.00	0	2820.37	70.3334	128.0	9.00	23.40	4L
G.320.300.0325	32.0	3.00	3.25	90	2820.37	43.3237	128.0	12.75	23.40	4L
G.320.300.0450	32.0	3.00	4.50	180	2820.37	31.3027	128.0	16.50	23.40	4L
G.320.300.0575	32.0	3.00	5.75	270	2820.37	24.5036	128.0	20.25	23.40	4L
G.320.300.0700	32.0	3.00	7.00	0	2820.37	20.1168	128.0	24.00	23.40	4L
G.320.300.0825	32.0	3.00	8.25	90	2820.37	17.0725	128.0	27.75	23.40	4L
G.320.300.0950	32.0	3.00	9.50	180	2820.37	14.8284	128.0	31.50	23.40	4L
G.320.300.1075	32.0	3.00	10.75	270	2820.37	13.0997	128.0	35.25	23.40	4L
G.330.340.1475	33.0	3.40	14.75	270	4519.00	16.7370	132.0	53.55	21.00	4L
G.341.270.0975	34.1	2.70	9.75	270	2373.00	8.7889	136.4	29.03	22.60	4L
G.342.290.0700	34.2	2.90	7.00	0	3164.00	17.5778	136.8	23.20	21.80	4L
G.344.320.0800	34.4	3.20	8.00	0	3616.00	20.0889	137.6	28.80	22.50	4L
G.346.360.0200	34.6	3.60	2.00	0	4777.41	136.4974	138.4	10.80	24.60	4L
G.346.360.0325	34.6	3.60	3.25	90	4777.41	84.1093	138.4	15.30	24.60	4L
G.346.360.0450	34.6	3.60	4.50	180	4777.41	60.7041	138.4	19.80	24.60	4L
G.346.360.0575	34.6	3.60	5.75	270	4777.41	47.4892	138.4	24.30	24.60	4L
G.346.360.0700	34.6	3.60	7.00	0	4777.41	39.0311	138.4	28.80	24.60	4L
G.346.360.0825	34.6	3.60	8.25	90	4777.41	33.1075	138.4	33.30	24.60	4L
G.346.360.0950	34.6	3.60	9.50	180	4777.41	28.7623	138.4	37.80	24.60	4L
G.346.360.1075	34.6	3.60	10.75	270	4777.41	25.4118	138.4	42.30	24.60	4L
G.348.270.1250	34.8	2.70	12.50	180	2373.00	6.5917	139.2	36.45	23.00	4L
G.355.400.0200	35.5	4.00	2.00	0	6165.41	195.1079	142.0	12.00	24.70	4N
G.355.400.0325	35.5	4.00	3.25	90	6165.41	120.1834	142.0	17.00	24.70	4N
G.355.400.0450	35.5	4.00	4.50	180	6165.41	86.8368	142.0	22.00	24.70	4N

Reference number	External diameter (mm)	Wire diameter (mm)	Number of coils	Leg position	Max Torque (Nmm)	Spring rate (Nmm/deg)	Leg length (mm)	Corpse Length (mm)	Max Shaft (mm)	Tariff code
G.355.400.0575	35.5	4.00	5.75	270	6165.41	67.9759	142.0	27.00	24.70	4N
G.355.400.0700	35.5	4.00	7.00	0	6165.41	55.7956	142.0	32.00	24.70	4N
G.355.400.0825	35.5	4.00	8.25	90	6165.41	47.3534	142.0	37.00	24.70	4N
G.355.400.0950	35.5	4.00	9.50	180	6165.41	41.1302	142.0	42.00	24.70	4N
G.355.400.1075	35.5	4.00	10.75	270	6165.41	36.3312	142.0	47.00	24.70	4N
G.364.290.0975	36.4	2.90	9.75	270	3164.00	11.7185	145.6	31.18	23.80	4L
G.372.290.1250	37.2	2.90	12.50	180	3164.00	8.7889	148.8	39.15	24.60	4L
G.379.340.0800	37.9	3.40	8.00	0	4519.00	25.1056	151.6	30.60	24.80	4L
G.385.320.1075	38.5	3.20	10.75	270	3616.00	13.3926	154.0	37.60	25.70	4L
G.405.400.0200	40.5	4.00	2.00	0	6165.41	168.4538	162.0	12.00	29.20	4N
G.405.400.0325	40.5	4.00	3.25	90	6165.41	103.7948	162.0	17.00	29.20	4N
G.405.400.0450	40.5	4.00	4.50	180	6165.41	74.9139	162.0	22.00	29.20	4N
G.405.400.0575	40.5	4.00	5.75	270	6165.41	58.6623	162.0	27.00	29.20	4N
G.405.400.0700	40.5	4.00	7.00	0	6165.41	48.1673	162.0	32.00	29.20	4N
G.405.400.0825	40.5	4.00	8.25	90	6165.41	40.8847	162.0	37.00	29.20	4N
G.405.400.0950	40.5	4.00	9.50	180	6165.41	35.4946	162.0	42.00	29.20	4N
G.405.400.1075	40.5	4.00	10.75	270	6165.41	31.3761	162.0	47.00	29.20	4N
G.408.320.1450	40.8	3.20	14.50	180	3616.00	10.0444	163.2	49.60	27.50	4L
G.422.340.1075	42.2	3.40	10.75	270	4519.00	16.7370	168.8	39.95	28.20	4L
G.446.340.1350	44.6	3.40	13.50	180	4519.00	12.5528	178.4	49.30	30.20	4L